


## NTC Thermistors, SMD Chip



### FEATURES

- Extended resistance values available in standard sizes
- Wraparound Ni barrier terminations with 100 % Sn (or Sn90Pb10)
- Allows design flexibility for use with hybrid circuitry
- Available in bulk or tape and reel packaging
- High-density monolithic construction with glass overcoat
- Compliant to RoHS directive 2002/95/EC
- Halogen-free according to IEC 61249-2-21 definition



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**

| QUICK REFERENCE DATA                                     |                                    |
|--|------------------------------------|
| PARAMETER  | VALUE                              |
| Resistance value at 25 °C                                | 1.0 kΩ to 350 kΩ                   |
| Tolerance on $R_{25}$ - value                            | ± 1 %, ± 2 %, ± 3 %, ± 5 %, ± 10 % |
| $B_{25/75}$ value  | 3181K to 4247K                     |
| Tolerance on $B_{25/85}$ - value                         | ± 3 %                              |
| Operating temperature range at zero power (intermittent) | - 40 °C to + 125 °C (150 °C)       |


### APPLICATIONS

- Temperature sensing, protection and compensation in automotive, industrial, telecom and consumer applications. Examples are:
  - Battery chargers
  - Power suppliers
  - Office equipment
  - LCD compensation
  - In-car entertainment

| NTHS PRODUCT DATA AND $R_{25}$ RESISTANCE RANGE AVAILABILITY |                 |           |               |               |               |               |                                |
|--|-----------------|-----------|---------------|---------------|---------------|---------------|--------------------------------|
| CURVE  | $B_{25/75}$ (K) | TCR (%/K) | NTHS0402 (kΩ) | NTHS0603 (kΩ) | NTHS0805 (kΩ) | NTHS1206 (kΩ) | $R_{25} \pm$ TOL. AVAILABILITY |
| 3  | 3181            | - 3.70    | -             | 1 to 2        | 1 to 1.5      | 1 to 2        | 5, 10                          |
| 6  | 3254            | - 3.60    | -             | 2.5 to 4.7    | 2 to 3.3      | 2.7 to 3.5    | 5, 10                          |
| 2  | 3477            | - 3.83    | 10 to 12      | 6.8 to 12     | 4.7 to 10     | 6 to 10       | 3, 5, 10                       |
| 10   | 3500            | - 3.90    | 18 to 25      | 12 to 20      | 6 to 12       | 10 to 20      | 3, 5, 10                       |
| 11   | 3700            | - 4.00    | 30 to 34      | 22 to 32      | 15 to 30      | 20 to 33      | 3, 5, 10                       |
| 5  | 3890            | - 4.30    | 47 to 50      | 38 to 57      | 35 to 50      | 30 to 44      | 3, 5, 10                       |
| 1  | 3964            | - 4.40    | 68 to 100     | 50 to 100     | 33 to 78      | 38 to 100     | 1, 2, 3, 5, 10                 |
| 17   | 4064            | - 4.54    | 250           | 150 to 220    | 100 to 200    | 100 to 220    | 3, 5, 10                       |
| 4  | 4247            | - 4.68    | 350           | 250 to 350    | 200 to 300    | 200 to 330    | 3, 5, 10                       |
| Maximum dissipation at 25 °C in mW                           |                 |           | 80            | 125           | 210           | 280           |                                |
| Dissipation factor in mW/K                                   |                 |           | 2.0           | 3.0           | 3.5           | 4.0           |                                |

### Note

- Typical resistance vs. temperature conversion data can be found at [www.vishay.com/doc?33011](http://www.vishay.com/doc?33011)



**DIMENSIONS** in inches (millimeters)



| PART NUMBER | L                                | W                              | BW                              |
|-------------|----------------------------------|--------------------------------|---------------------------------|
| NTHS0402    | 0.040 ± 0.004<br>(1.016 ± 0.102) | 0.022 ± 0.006<br>(0.5 ± 0.051) | 0.010 ± 0.004<br>(0.25 ± 0.102) |
| NTHS0603    | 0.063 ± 0.008<br>(1.6 ± 0.20)    | 0.031 ± 0.008<br>(0.80 ± 0.20) | 0.010 ± 0.006<br>(0.25 ± 0.15)  |
| NTHS0805    | 0.079 ± 0.008<br>(2.00 ± 0.20)   | 0.049 ± 0.008<br>(1.25 ± 0.20) | 0.012 ± 0.006<br>(0.30 ± 0.15)  |
| NTHS1206    | 0.126 ± 0.008<br>(3.20 ± 0.20)   | 0.063 ± 0.008<br>(1.60 ± 0.20) | 0.018 ± 0.008<br>(0.46 ± 0.20)  |

**Note**

- Thickness of the part is depending on size and resistance value. Please consult the factory for more information on individual types at [thermistor1@vishay.com](mailto:thermistor1@vishay.com)



## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.