## Honeywell

### **Honeywell Sensing and Control**

Home> Products > Packaged Temperature Probes> 500 > Product Page

#### Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback



500 Series immersion temperature probe

**Potential Applications** 

Actual product appearance may vary.

#### Features

Wide selection of housing options Choice of custom or existing designs Operating temperature range design available from -60 °C to 300 °C {76 °F to 572 °F]

#### Automotive White goods Communications Medical Fire detection Computers Instrumentation test equipment Microwave oven probes Bulk freight refrigeration Digital thermometers Drinking and vending machines Military Aerospace

# Login as Rep/AD Login as Guest Login to Digital University Veryword Search Search for product and support information. All Sensing and Controner

My Links

Login to iCOM

Product Search

Part number search:

Use (\*) to expand search

**Specification Search** 

#### Description

The 500 Series Probes represents a full range of thermistor and RTDbased temperature sensors. These assemblies have been designed for use in specific applications. Housings may accommodate air/gas, immersion or surface sensing requirements. Housing material ranges from all plastic to all metal. In addition to custom configurations, the customer may also choose from a variety of existing designs.

Supporting Documentation None Available

Product Specifications	
Thermistor Type	NTC
Temperature Sensing Type	Immersion
Nominal Resistance at 25 °C [77 ° F]	10,000 Ohm
Tolerance	± 1.0 °C [1.8 °F]
Accuracy	0 °C to 80 °C [32 °F to 176 °F]
R-T Curve	16
Operating Temperature Range	- 60 °C to 150 °C [ -76 °F to 302 ° F]
Housing Material	Brass
Mechanical Interface	1/8 - 27 NPT thread
Electrical Interface	Lead wires with connector(s)
Lead Material	18 Gauge polyolefin insulation
Lead Length	152 mm [6 in]
Connector Type	Packard 15300027
Time Constant in Water at 0.914 m/s [3 ft/s]	15.0 s
Dissipation Constant in Water at 0.914 m/s [3 ft/s]	5 mW/°C
Availability	Global
Series Name	500

Terms & Conditions | Privacy Statement | Site Map