


Surface Mount Oscillator



The XOSM-573 series is an ultra miniature package clock oscillator with dimensions 7.0 mm x 5.0 mm x 1.9 mm. It is mainly used in portable PC and telecommunication devices and equipment

FEATURES

- Size: 7.0 x 5.0 x 1.9 (mm)
- Miniature package
- Tri-state enable/disable
- TTL/HCMOS compatible
- Tape and reel
- I_R re-flow
- 3.3 V input voltage
- Compliant to RoHS Directive 2002/95/EC


RoHS
COMPLIANT

| STANDARD ELECTRICAL SPECIFICATIONS | | | |
|------------------------------------|--------------------------------|---------------------------|---|
| PARAMETER | SYMBOL | CONDITION | VALUE |
| Frequency range | F _O | - | 1.500 MHz to 100.000 MHz |
| Frequency stability ⁽¹⁾ | | all conditions | ± 25 ppm, ± 50 ppm, ± 100 ppm |
| Operating temperature range | T _{OPR} | - | 0 °C to 70 °C |
| | | | - 40 °C to + 85 °C (option) |
| Storage temperature range | T _{STG} | - | - 55 °C to + 125 °C |
| Power supply voltage | V _{DD} | - | 3.3 V ± 10 % |
| Aging (first year) | | 25 °C ± 3 °C | ± 5 ppm |
| Supply current | I _{DD} | 1.500 MHz to 20.000 MHz | 10 mA max. |
| | | 20.001 MHz to 50.000 MHz | 20 mA max. |
| | | 50.001 MHz to 67.000 MHz | 30 mA max. |
| | | 67.001 MHz to 100.000 MHz | 55 mA max. |
| Output symmetry | Sym | at ½ V _{DD} | 40 %/60 % (45 %/55 % option) |
| Rise/fall time | t _r /t _f | 1.500 MHz to 50.000 MHz | 6 ns |
| | | 50.001 MHz to 80.000 MHz | 4 ns |
| | | 80.001 MHz to 100.000 MHz | 2 ns |
| Output voltage | V _{OH} | - | 90 % V _{DD} min. |
| | V _{OL} | - | 10 % V _{DD} max. |
| Output load | | - | 2 TTL or 15 pF |
| Start-up time | t _s | - | 10 ms max. |
| Pin 1, tri-state function | | - | pin 1 = H or open (output active at pin 3) pin 1 = L (high impedance at pin 3) |

Note

⁽¹⁾ Include: 25 °C tolerance, operating temperature range, input voltage change, aging, load change, shock and vibration

| DIMENSIONS in inches [millimeters] | | | | | | | | | | | |
|------------------------------------|--|-----|------------|----|--------------|----|-----|----|--------|----|-----------------|
| | | | | | | | | | | | |
| | <table border="1"> <thead> <tr> <th>PIN</th> <th>CONNECTION</th> </tr> </thead> <tbody> <tr> <td>#1</td> <td>TRI-STATE/NC</td> </tr> <tr> <td>#2</td> <td>GND</td> </tr> <tr> <td>#3</td> <td>OUTPUT</td> </tr> <tr> <td>#4</td> <td>V_{DD}</td> </tr> </tbody> </table> | PIN | CONNECTION | #1 | TRI-STATE/NC | #2 | GND | #3 | OUTPUT | #4 | V _{DD} |
| PIN | CONNECTION | | | | | | | | | | |
| #1 | TRI-STATE/NC | | | | | | | | | | |
| #2 | GND | | | | | | | | | | |
| #3 | OUTPUT | | | | | | | | | | |
| #4 | V _{DD} | | | | | | | | | | |

Note

- A 0.01 µF bypass capacitor should be placed between V_{DD} (pin 4) and GND (pin 2) to minimize power supply line noise

ORDERING INFORMATION

| XOSM-573 | B | R | E | 50M | e4 |
|----------|---|---|--|---------------|----------------------------------|
| MODEL | FREQUENCY STABILITY AA = 0.0025 % (25 ppm) A = 0.005 % (50 ppm) B = 0.01 % (100 ppm) standard | OTR blank = standard R = - 40 °C to + 85 °C | ENABLE/DISABLE E = disable to tri-state | FREQUENCY/MHz | JEDEC LEAD (Pb)-FREE standard |

GLOBAL PART NUMBER



GLOBAL PART NUMBERING

| MODEL NUMBER | FREQUENCY STABILITY | OPERATING TEMPERATURE (OTR) | ENABLE/DISABLE | PACKAGE CODE | OPTION | FREQUENCY |
|---|---|---|---|--|--|---|
| XO53 = XO-53 XO54 = XO-54 XO34 = XO-543 XO52 = XO-52 XO32 = XO-523 XO5M = XOSM-52 XO63 = XOSM-533 XO62 = XOSM-532 XO61 = XOSM-531 XO57 = XOSM-57 XO37 = XOSM-573 XO27 = XOSM-572 XO17 = XOSM-571 XO55 = XOSM-55 XO35 = XOSM-553 | C = 0.01 % (100 ppm) D = 0.005 % (50 ppm) E = 0.0025 % (25 ppm) | T = 0 °C to + 70 °C R = - 40 °C to + 85 °C | F = pin 1 open E = disable to tristate | Tape and reel H = RF7 Bulk A = B04 (XO63, XO62, XO61) C = D06 (XO57, XO37, XO27, XO17) D = D07 (XO53, XO54, XO34, XO55, XO35) L = D08 (XO52, XO32, XO5M) | NA = no additional options 60 = 45/55 symmetry Contact factory for all other options | 4M = 4 MHz 40M = 40 MHz 100M = 100 MHz 12M288 = 12.288 MHz M is used as decimal place holder in frequency |

Example: XO52CTELNA40M

PART MARKING

Line 1: M2809XXXXX (part number)
 Line 2: XX.XXXXM (frequency)
 Line 3: yywwvv (date/factory code)



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.