



# ATS-49 and MP-1 Crystals



**MP-1 (HC-49/U) 00.0000 MHz** (customer specified frequency)

**MP-1-R (HC-49/U) 00.0000 MHz** (RoHS Compliant and customer specified frequency)

M1002Sxxx - Contact factory for datasheet.



Equivalent Series Resistance (ESR), Max.	ATS-49
Fundamental (AT-cut)	
3.579 to 3.999 MHz	200 Ω
4.000 to 4.999 MHz	150 Ω
5.000 to 5.999 MHz	120 Ω
6.000 to 9.999 MHz	100 Ω
10.000 to 13.999 MHz	80 Ω
14.000 to 40.000 MHz	50 Ω
Fundamental (BT-cut)	
24.000 to 50.000 MHz	100 Ω
Third Overtones (AT-cut)	
25.000 to 39.999 MHz	100 Ω
40.000 to 72.000 MHz	80 Ω

Equivalent Series Resistance (ESR), Max.	MP-1
Fundamental (AT-cut)	
1.8432 to 1.999 MHz	700 Ω
2.000 to 2.399 MHz	600 Ω
2.400 to 3.299 MHz	400 Ω
3.300 to 3.569 MHz	140 Ω
3.570 to 3.999 MHz	100 Ω
4.000 to 5.999 MHz	75 Ω
6.000 to 7.999 MHz	50 Ω
8.000 to 10.999 MHz	40 Ω
11.000 to 14.999 MHz	30 Ω
15.000 to 19.999 MHz	25 Ω
20.000 to 34.000 MHz	25 Ω
Third Overtones (AT-cut)	
20.000 to 49.999 MHz	40 Ω
50.000 to 75.000 MHz	50 Ω
Fifth Overtones (AT-cut)	
50.000 to 125.000 MHz	90 Ω
Seventh Overtones (AT-cut)	
125.000 to 200.000 MHz	150 Ω



**\*ATS-49 00.0000 MHz** (customer specified)

**\*ATS-49-R 00.0000 MHz** (RoHS Compliant and customer specified frequency)

M1004Sxxx - Contact factory for datasheet.

MtronPTI reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application.

Please see [www.mtronpti.com](http://www.mtronpti.com) for our complete offering and detailed datasheets. Contact us for your application specific requirements: MtronPTI 1-800-762-8800.

# ATS-49 and MP-1 Crystals



MtronPTI ATS-49 Options	
Order by part number listed followed by the desired frequency.	
Part No.	Description
397-030	Fundamental, 20pF load, $\pm 30$ ppm tolerance, $\pm 50$ ppm stability, $-10^{\circ}\text{C}$ to $+70^{\circ}\text{C}$ operating temperature
397-040	Fundamental, series resonant, $-10^{\circ}\text{C}$ to $+70^{\circ}\text{C}$ operating temperature
397-310	Fundamental, 18pF load, $-40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$ operating temperature
482-010	Fundamental, base insulator
482-040	Fundamental, series resonant, base insulator
482-740	Fundamental, series resonant, $-40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$ operating temperature
483-240	3 <sup>rd</sup> overtone, series resonant, $\pm 30$ ppm tolerance, $\pm 50$ ppm stability, $-40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$ operating temperature
493-040	3 <sup>rd</sup> overtone, series resonant
Balance of specifications same as shown in "Electrical Specifications"	
Contact the factory for options not listed above.	

	PARAMETER	Symbol	Min.	Typ.	Max.	Units	Condition/Notes	
Electrical Specifications	Frequency Range	F	1.8432 3.579545		200 72	MHz MHz	MP-1 ATS-49	
	Frequency Tolerance	F/F	-30		+30	ppm		
	Frequency Stability	$\Delta F/F$	-50		+50	ppm	See Note 1	
	Operating Temperature	$T_A$	-10		+70	$^{\circ}\text{C}$		
	Storage Temperature	$T_S$	-55		+125		$^{\circ}\text{C}$	
	Aging Per Year			$\pm 5$	$\pm 5$			
	Load Capacitance	$C_L$		18		pF	See Note 2	
	Shunt Capacitance	$C_O$			7	pF		
	ESR		See ESR Tables					
	Drive Level	$D_L$	50 25	100 100	1 500	mW $\mu\text{W}$	MP-1 ATS-49	
Insulation Resistance	$I_R$	500			MOhms			
Environmental	Mechanical Shock	MIL-STD-202, Method 213, C (100 g's)						
	Vibration	MIL-STD-202, Method 201 & 204 (10 g's from 10-2000 Hz)						
	Thermal Cycle	MIL-STD-883, Method 1010, B ( $-55^{\circ}\text{C}$ to $125^{\circ}\text{C}$ , 15 min dwell, 10 cycles)						
	Hermeticity	MIL-STD-202, Method 112 (must meet $1 \times 10^{-8}$ )						
	Solderability	Per EIAJ-STD-002						
Max Wave Soldering Conditions	+260 $^{\circ}\text{C}$ for 10 secs. Max.							

Note 1: BT cut fundamentals from 24.000 to 40.000 MHz have a stability of  $\pm 100$  ppm (ATS-49)

Note 2: Series resonant designated "SR" prefix (i.e., SRATS-49 or SRMP-1)

MtronPTI reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application.

Please see [www.mtronpti.com](http://www.mtronpti.com) for our complete offering and detailed datasheets. Contact us for your application specific requirements: MtronPTI 1-800-762-8800.