



Search:



Products

Catalogs

Search

Customer Support

About Cannon

Home



## D Subminiature Accessories

PART NUMBER: DC121073-52

Image Disclaimer:

Please use Customer Drawing for design activity: line art and other pictures are general representations of product dimensions.

[View Line Drawings](#)



- [Sales Support](#)
- [Ask a Specialist](#)
- [Product Home](#)
- [Stock Check](#)

|                             |   |
|-----------------------------|---|
| <b>Product Group</b>        | D Subminiature Accessories  |
| <b>Where Sold</b>           | Americas, Asia Pacific, Europe  |
| <b>D Sub Accessory type</b> | EMI Shielded Endbell  |
| <b>Application Type</b>     | Commercial  |
| <b>Shell Size</b>           | DC  |
| <b>Layout</b>               | 37  |
| <b>Material</b>             | Thermoplastic, UL 94V-0 Rated   |
| <b>Cable Exit</b>           | 40 Degree Cable Exit  |
| <b>Finish/Treatment</b>     | Nickel over copper  |
| <b>Attenuation</b>          | -49 dB at 100 MHz   |
| <b>Temperature Range</b>    | -20°C to 80°C   |
| <b>Cable Entry</b>          | Ø11,00 (.433)   |
| <b>Dimension B</b>          | 74,50 (2.933) ±0,30 (.012)  |
| <b>Dimension C</b>          | 57,51 (2.264) ±0,30 (.012)  |
| <b>Dimension D</b>          | 16,00 (.630) ±0,30 (.012)   |
| <b>Dimension E</b>          | 42,01 (1.654) ±0,20 (.008)  |
| <b>Min. Cable Diameter</b>  | Ø6,50 (.256)  |
| <b>Max. Cable Diameter</b>  | Ø11,00 (.433)   |
| <b>Note 1</b>               | Kit consists of 1 front shell, 1 rear shell, 1 cable clamp, 2 screws. |
| <b>Note 2</b>               | Order optional locking hardware separately.                           |
| <b>Footnote</b>             | Dimension are shown in mm (inch). Dimensions subject to change.       |
| <b>For more information</b> | Please Contact Cannon Sales Department.                               |



