

This document was generated on 02/28/2011 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>0747280415</u>		_
Status:	Active		
Overview:			
scription: 1-by-4 Small Form-factor Pluggable (SFP) Ganged Cage, Elastomeric Gaske		Pluggable (SFP) Ganged Cage, Elastomeric Gasket, Press-fit	
Documents:			
<u>3D Model</u>		<u>Test Summary TS-73927-0002 (PDF)</u>	
<u>Drawing (PDF)</u>		Test Summary TS-74728-0415 (PDF)	I '` \ 'I ⊳ >"
Product Specificatio	<u>n PS-74728-001 (PDF)</u>	RoHS Certificate of Compliance (PDF)	
			Series
General			image - Reference only
Product Family		I/O Connectors	
Series		<u>74728</u>	EU RoHS China RoHS
Application		Module-to-Board	ELV and RoHS
Comments		PCB Thickness: 1.6mm (.062") Single Sided Use &	Compliant
		3.00mm (.116") Belly-to-belly Use 4 Ports	REACH SVHC
Component Type		Cage Assembly	Not Reviewed
Overview		sfp lightpipe cover assembly	Low-Halogen Status
Product Name		SFP	Not Reviewed
Type		N/A	Need more information on product
			environmental compliance?
Physical			•
Circuits (Loaded)		N/A	Email productcompliance@molex.com
Keying to Mating Part		None	For a multiple part number RoHS Certifica
Lock to Mating Part		Yes	Compliance, <u>click here</u>
Material - Metal		Copper-Nickel-Zinc	
Material - Plating Mating		Unplated	Please visit the <u>Contact Us</u> section for any
Orientation		Right Angle	non-product compliance questions.
PCB Retention		Yes	
Packaging Type		Tray	
Panel Mount		No	
Pitch - Mating Interface		N/A	Search Parts in this Series
Polarized to Mating Part		Yes	74728Series
Ports		4	<u></u>
Surface Mount Compatible (SMC)		No	Annihestian Teeling EAO
Temperature Range - Operating		-55°C to +105°C	Application Tooling <u>FAQ</u>
Termination Interface: Style		Through Hole - Compliant Pin	Tooling specifications and manuals are
			found by selecting the products below.
Electrical			Crimp Height Specifications are then contained in the Application Tooling
Current - Maximum per Contact		N/A	
Grounding to Panel		N/A	Specification document.
Shielded		Yes	Global Description Product #
	Dete		Insertion Tool for 1- 0622029780
Solder Process Data			by-4 Small Form-
Process Temperature max. C		70	Factor Pluggable
Material Info			(SFP+)
			Removal Tool for 1- 0622029790
Reference - Dra	wing Numbers		by-4 Small Form-
Product Specification		PS-74728-001	Factor Pluggable
Sales Drawing		SD-74728-415	(SFP+)
Test Summary		TS-73927-0002, TS-74728-0415	

This document was generated on 02/28/2011 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION