Our commitment. Your advantage.

Documentation

Resources

My Account **Customer Support**

Home > Products > By Type > AMPLIMITE D - Subminiature > Product Feature Selector > Product Details

5205732 -1 Product Details



5205732

Active

Cable Clamps

Always EU RoHS/ELV Compliant (Statement of Compliance

Product Highlights:

- Backshell/Cable Clamp
- Cable Clamp Type = Clam Shell
- Straight(180°)/45° Cable Exit Angle
- Cable Insulation Diameter = 15.24 mm
- Shell Size = 5

View all Features | Find Similar <u>Products</u>



Quick Links

Check Pricing & Availability Search for Tooling Product Feature Selector Contact Us About This Product

Documentation & Additional Information

Product Drawings:

² SELF TAPPED 45/180 DEG CABLE SUPPORT CLAMSHELL, SIZE. (PDF, English)

Catalog Pages/Data Sheets:

? None Available

Product Specifications:

? None Available

Application Specifications:

? None Available

Instruction Sheets:

? Cablej Clamp Assemblies for AMPLIMITE HD -20 and HD -2... (PDF, English)

CAD Files:

? None Available

List all Documents

Additional Information:

Product Line Information

Related Products:

? Tooling

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Backshell/Cable Clamp
- ? Cable Clamp Type = Clam Shell
- ? Shell Size = 5
- ? Shielded = No
- ? Screws and Retainer Clips = Without
- ? Grommets = Without
- ? Thread Size = 6 -32
- ? Product Series = HDP Metal Shell
- ? Clam Shell Length = Standard
- ? Comment = All parts are packaged unassembled.

Body Related Features:

- ? Cable Exit Angle = Straight(180°)/45°
- ? Cable Insulation Diameter (mm [in]) [0.600]
- ? Cable Clamp Material = Thermoplastic
- ? Shield Plating = None

Industry Standards:

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- 2 Lead Free Solder Processes = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Packaging Related Features:

? Packaging Method = Individual Kit

? Brand = AMP

Provide Website Feedback | Contact Customer Support