



Search:



Products

Catalogs

Search

Customer Support

About Cannon

Home



D Subminiature Accessories

PART NUMBER: DB121073-51

Image Disclaimer:

Please use Customer Drawing for design activity: line art and other pictures are general representations of product dimensions.

[View Line Drawings](#)



- [Sales Support](#)
- [Ask a Specialist](#)
- [Product Home](#)
- [Stock Check](#)

Product Group	D Subminiature Accessories
Where Sold	Europe, Asia Pacific, Americas
D Sub Accessory type	EMI Shielded Endbell
Application Type	Commercial
Shell Size	DB
Layout	25
Material	Thermoplastic, UL 94V-0 Rated
Cable Exit	40 Degree Cable Exit
Finish/Treatment	Nickel over copper
Attenuation	-49 dB at 100 MHz
Temperature Range	-20°C to 80°C
Cable Entry	Ø11,00 (.433)
Dimension B	57,99 (2.283) ±0,30 (.012)
Dimension C	41,00 (1.614) ±0,30 (.012)
Dimension D	16,00 (.630) ±0,30 (.012)
Dimension E	42,01 (1.654) ±0,20 (.008)
Min. Cable Diameter	Ø6,50 (.256)
Max. Cable Diameter	Ø11,00 (.433)
Note 1	Kit consists of 1 front shell, 1 rear shell, 1 cable clamp, 2 screws.
Note 2	Order optional locking hardware separately.
Footnote	Dimension are shown in mm (inch). Dimensions subject to change.
For more information	Please Contact Cannon Sales Department.



