



AS85049/11 and MS3437B Environmental Backshells

Glenair Connector Designator A

MIL-DTL-5015 Series 3400,
 MIL-DTL-26482 Series 2,
 AS81703 Series 3,
 MIL-DTL-83723 Series I & III,
 40M39569, DEF 5326-3,
 EN 2997, EN 3646,
 ESC 10, ESC 11, LN 29504,
 NFC93422 Series HE302,
 PAN 6432-1, PAN 6432-2,
 PATT 602

M85049/11-21 N


Basic Part No. ————
 Dash No. (Table II) ————

Finish and Material
 B = Black Cadmium, Stainless Steel
 N = Electroless Nickel, Aluminum
 S = Passivated Stainless Steel
 W = 1,000 Hour Cadmium Olive Drab Over Electroless Nickel, Aluminum


MS3437B 21 N

Basic Part No. ————
 Dash No. (Table II) ————

Superceded Part Number
 Finish (Material is Aluminum Only)
 A = Cadmium Olive Drab over Nickel
 C = Cadmium Olive Drab
 N = Electroless Nickel



STYLE 2



STYLE 1

TABLE I

| Shell Size | A Thread Class 2B | C Dia Max |
|------------|-------------------|--------------|
| 3 | .562 - 24 UNEF | .669 (17.0) |
| 8 | .500 - 20 UNF | .617 (15.7) |
| 10 | .625 - 24 UNEF | .734 (18.6) |
| 12 | .750 - 20 UNEF | .858 (21.8) |
| 14 | .875 - 20 UNEF | .984 (25.0) |
| 16 | 1.000 - 20 UNEF | 1.112 (28.2) |
| 18 | 1.062 - 18 UNEF | 1.218 (30.9) |
| 20 | 1.188 - 18 UNEF | 1.345 (34.2) |
| 22 | 1.313 - 18 UNEF | 1.468 (37.3) |
| 24 | 1.438 - 18 UNEF | 1.593 (40.5) |
| 28 | 1.750 - 18 UNS | 1.969 (50.0) |
| 32 | 2.000 - 18 UNS | 2.219 (56.4) |
| 36 | 2.250 - 16 UN | 2.469 (62.7) |
| 40 | 2.500 - 16 UN | 2.719 (69.1) |
| 44 | 2.750 - 16 UN | 2.969 (75.4) |
| 48 | 3.000 - 16 UN | 3.219 (81.8) |
| 61 | 1.500 - 18 UNEF | 1.653 (42.0) |

1. For complete dimensions see applicable Military Specification.
2. Metric dimensions (mm) are indicated in parentheses.
3. Cable range is defined as the accommodations range for the wire bundle or cable. Dimensions shown are not intended for inspection criteria.
4. When maximum cable entry is exceeded, Style 2 will be supplied.

AS85049/11 and MS3437B Environmental Backshells



Environmental
Backshells

TABLE II

| Dash No. | Shell Size | Style | E | | K | | L | | Cable Range | | | | M85049/42 |
|----------|------------|-------|-------|---------|-------|--------|-------|--------|-------------|--------|-------|--------|-----------|
| | | | Max | (in) | Ref. | (in) | Max | (in) | Min | (in) | Max | (in) | Ref |
| 01 | 3 | 1 | 2.125 | (54.0) | 1.027 | (26.1) | .957 | (24.3) | .125 | (3.2) | .250 | (6.4) | 4 |
| 02 | 3 | 1 | 3.125 | (79.4) | 1.027 | (26.1) | .957 | (24.3) | .125 | (3.2) | .250 | (6.4) | 4 |
| 03 | 3 | 2 | 2.875 | (73.0) | 1.027 | (26.1) | 1.145 | (29.1) | .250 | (6.4) | .437 | (11.1) | 6 |
| 04 | 3 | 2 | 3.875 | (98.4) | 1.027 | (26.1) | 1.145 | (29.1) | .250 | (6.4) | .437 | (11.1) | 6 |
| 05 | 8 | 1 | 2.125 | (54.0) | 1.027 | (26.1) | .957 | (24.3) | .125 | (3.2) | .250 | (6.4) | 4 |
| 06 | 8 | 1 | 3.125 | (79.4) | 1.027 | (26.1) | .957 | (24.3) | .125 | (3.2) | .250 | (6.4) | 4 |
| 07 | 8 | 2 | 2.875 | (73.0) | 1.027 | (26.1) | 1.145 | (29.1) | .250 | (6.4) | .437 | (11.1) | 6 |
| 08 | 8 | 2 | 3.875 | (98.4) | 1.027 | (26.1) | 1.145 | (29.1) | .250 | (6.4) | .437 | (11.1) | 6 |
| 09 | 10 | 1 | 2.125 | (54.0) | 1.027 | (26.1) | .957 | (24.3) | .125 | (3.2) | .312 | (7.9) | 4 |
| 10 | 10 | 1 | 3.125 | (79.4) | 1.027 | (26.1) | .957 | (24.3) | .125 | (3.2) | .312 | (7.9) | 4 |
| 11 | 10 | 2 | 2.875 | (73.0) | 1.027 | (26.1) | 1.145 | (29.1) | .250 | (6.4) | .437 | (11.1) | 6 |
| 12 | 10 | 2 | 3.875 | (98.4) | 1.027 | (26.1) | 1.145 | (29.1) | .250 | (6.4) | .437 | (11.1) | 6 |
| 13 | 12 | 1 | 2.125 | (54.0) | 1.027 | (26.1) | 1.145 | (29.1) | .250 | (6.4) | .437 | (11.1) | 6 |
| 14 | 12 | 1 | 3.125 | (79.4) | 1.027 | (26.1) | 1.145 | (29.1) | .250 | (6.4) | .437 | (11.1) | 6 |
| 15 | 12 | 2 | 2.875 | (73.0) | 1.027 | (26.1) | 1.332 | (33.8) | .350 | (8.9) | .625 | (15.9) | 10 |
| 16 | 12 | 2 | 3.875 | (98.4) | 1.027 | (26.1) | 1.332 | (33.8) | .350 | (8.9) | .625 | (15.9) | 10 |
| 17 | 14 | 1 | 2.125 | (54.0) | 1.027 | (26.1) | 1.332 | (33.8) | .350 | (8.9) | .575 | (14.6) | 10 |
| 18 | 14 | 1 | 3.125 | (79.4) | 1.027 | (26.1) | 1.332 | (33.8) | .350 | (8.9) | .575 | (14.6) | 10 |
| 19 | 14 | 2 | 2.875 | (73.0) | 1.059 | (26.9) | 1.551 | (39.4) | .500 | (12.7) | .750 | (19.1) | 12 |
| 20 | 14 | 2 | 3.875 | (98.4) | 1.059 | (26.9) | 1.551 | (39.4) | .500 | (12.7) | .750 | (19.1) | 12 |
| 21 | 16 | 1 | 2.125 | (54.0) | 1.059 | (26.9) | 1.551 | (39.4) | .500 | (12.7) | .700 | (17.8) | 12 |
| 22 | 16 | 1 | 3.125 | (79.4) | 1.059 | (26.9) | 1.551 | (39.4) | .500 | (12.7) | .700 | (17.8) | 12 |
| 23 | 16 | 2 | 2.875 | (73.0) | 1.156 | (29.4) | 1.770 | (45.0) | .625 | (15.9) | .937 | (23.8) | 16 |
| 24 | 16 | 2 | 3.875 | (98.4) | 1.156 | (29.4) | 1.770 | (45.0) | .625 | (15.9) | .937 | (23.8) | 16 |
| 25 | 18 | 1 | 2.125 | (54.0) | 1.027 | (26.1) | 1.332 | (33.8) | .350 | (8.9) | .625 | (15.9) | 10 |
| 26 | 18 | 1 | 3.125 | (79.4) | 1.027 | (26.1) | 1.332 | (33.8) | .350 | (8.9) | .625 | (15.9) | 10 |
| 27 | 18 | 1 | 2.125 | (54.0) | 1.059 | (26.9) | 1.551 | (39.4) | .500 | (12.7) | .750 | (19.1) | 12 |
| 28 | 18 | 1 | 3.125 | (79.4) | 1.059 | (26.9) | 1.551 | (39.4) | .500 | (12.7) | .750 | (19.1) | 12 |
| 29 | 18 | 2 | 2.875 | (73.0) | 1.156 | (29.4) | 1.770 | (45.0) | .625 | (15.9) | .937 | (23.8) | 16 |
| 30 | 18 | 2 | 3.875 | (98.4) | 1.156 | (29.4) | 1.770 | (45.0) | .625 | (15.9) | .937 | (23.8) | 16 |
| 31 | 20 | 1 | 3.125 | (79.4) | 1.027 | (26.1) | 1.332 | (33.8) | .350 | (8.9) | .625 | (15.9) | 10 |
| 32 | 20 | 1 | 4.125 | (104.8) | 1.027 | (26.1) | 1.332 | (33.8) | .350 | (8.9) | .625 | (15.9) | 10 |
| 33 | 20 | 1 | 3.125 | (79.4) | 1.059 | (26.9) | 1.551 | (39.4) | .500 | (12.7) | .750 | (19.1) | 12 |
| 34 | 20 | 1 | 4.125 | (104.8) | 1.059 | (26.9) | 1.551 | (39.4) | .500 | (12.7) | .750 | (19.1) | 12 |
| 35 | 20 | 2 | 3.875 | (98.4) | 1.156 | (29.4) | 1.770 | (45.0) | .625 | (15.9) | .937 | (23.8) | 16 |
| 36 | 20 | 2 | 4.875 | (123.8) | 1.156 | (29.4) | 1.770 | (45.0) | .625 | (15.9) | .937 | (23.8) | 16 |
| 37 | 20 | 2 | 3.875 | (98.4) | 1.375 | (34.9) | 2.113 | (53.7) | .875 | (22.2) | 1.250 | (31.8) | 20 |
| 38 | 20 | 2 | 4.875 | (123.8) | 1.375 | (34.9) | 2.113 | (53.7) | .875 | (22.2) | 1.250 | (31.8) | 20 |
| 39 | 22 | 1 | 3.125 | (79.4) | 1.027 | (26.1) | 1.332 | (33.8) | .350 | (8.9) | .625 | (15.9) | 10 |
| 40 | 22 | 1 | 4.125 | (104.8) | 1.027 | (26.1) | 1.332 | (33.8) | .350 | (8.9) | .625 | (15.9) | 10 |
| 41 | 22 | 1 | 3.125 | (79.4) | 1.059 | (26.9) | 1.551 | (39.4) | .500 | (12.7) | .750 | (19.1) | 12 |
| 42 | 22 | 1 | 4.125 | (104.8) | 1.059 | (26.9) | 1.551 | (39.4) | .500 | (12.7) | .750 | (19.1) | 12 |
| 43 | 22 | 1 | 3.125 | (79.4) | 1.156 | (29.4) | 1.770 | (45.0) | .625 | (15.9) | .937 | (23.8) | 16 |
| 44 | 22 | 1 | 4.125 | (104.8) | 1.156 | (29.4) | 1.770 | (45.0) | .625 | (15.9) | .937 | (23.8) | 16 |
| 45 | 22 | 2 | 3.875 | (98.4) | 1.375 | (34.9) | 2.113 | (53.7) | .875 | (22.2) | 1.250 | (31.8) | 20 |
| 46 | 22 | 2 | 4.875 | (123.8) | 1.375 | (34.9) | 2.113 | (53.7) | .875 | (22.2) | 1.250 | (31.8) | 20 |
| 47 | 24 | 1 | 3.125 | (79.4) | 1.059 | (26.9) | 1.551 | (39.4) | .500 | (12.7) | .750 | (19.1) | 12 |
| 48 | 24 | 1 | 4.125 | (104.8) | 1.059 | (26.9) | 1.551 | (39.4) | .500 | (12.7) | .750 | (19.1) | 12 |
| 49 | 24 | 1 | 3.125 | (79.4) | 1.156 | (29.4) | 1.770 | (45.0) | .625 | (15.9) | .812 | (20.6) | 16 |
| 50 | 24 | 1 | 4.125 | (104.8) | 1.156 | (29.4) | 1.770 | (45.0) | .625 | (15.9) | .812 | (20.6) | 16 |
| 51 | 24 | 1 | 3.125 | (79.4) | 1.156 | (29.4) | 1.770 | (45.0) | .625 | (15.9) | .937 | (23.8) | 16 |
| 52 | 24 | 1 | 4.125 | (104.8) | 1.156 | (29.4) | 1.770 | (45.0) | .625 | (15.9) | .937 | (23.8) | 16 |

Table continued on the next page.



AS85049/11 and MS3437B Environmental Backshells

TABLE II (Continued)

| Dash No. | Shell Size | Style | E | | K | | L | | Cable Range | | M85049/42 Ref | | |
|----------|------------|-------|-------|----------|-------|----------|-------|----------|-------------|--------|---------------|--------|----|
| | | | Max | (Inches) | Ref. | (Inches) | Max | (Inches) | Min | Max | | | |
| 53 | 24 | 2 | 3.875 | (98.4) | 1.375 | (34.9) | 2.113 | (53.7) | .875 | (22.2) | 1.250 | (31.8) | 20 |
| 54 | 24 | 2 | 4.875 | (123.8) | 1.375 | (34.9) | 2.113 | (53.7) | .875 | (22.2) | 1.250 | (31.8) | 20 |
| 55 | 28 | 1 | 3.125 | (79.4) | 1.059 | (26.9) | 1.551 | (39.4) | .500 | (12.7) | .750 | (19.1) | 12 |
| 56 | 28 | 1 | 4.125 | (104.8) | 1.059 | (26.9) | 1.551 | (39.4) | .500 | (12.7) | .750 | (19.1) | 12 |
| 57 | 28 | 1 | 3.125 | (79.4) | 1.156 | (29.4) | 1.770 | (45.0) | .625 | (15.9) | .937 | (23.8) | 16 |
| 58 | 28 | 1 | 4.125 | (104.8) | 1.156 | (29.4) | 1.770 | (45.0) | .625 | (15.9) | .937 | (23.8) | 16 |
| 59 | 28 | 1 | 3.125 | (79.4) | 1.375 | (34.9) | 2.113 | (53.7) | .875 | (22.2) | 1.250 | (31.8) | 20 |
| 60 | 28 | 1 | 4.125 | (104.8) | 1.375 | (34.9) | 2.113 | (53.7) | .875 | (22.2) | 1.250 | (31.8) | 20 |
| 61 | 28 | 1 | 3.125 | (79.4) | 1.500 | (38.1) | 2.363 | (60.0) | 1.000 | (25.4) | 1.375 | (34.9) | 24 |
| 62 | 28 | 1 | 4.125 | (104.8) | 1.500 | (38.1) | 2.363 | (60.0) | 1.000 | (25.4) | 1.375 | (34.9) | 24 |
| 63 | 32 | 1 | 3.125 | (79.4) | 1.156 | (29.4) | 1.770 | (45.0) | .625 | (15.9) | .937 | (23.8) | 16 |
| 64 | 32 | 1 | 4.125 | (104.8) | 1.156 | (29.4) | 1.770 | (45.0) | .625 | (15.9) | .937 | (23.8) | 16 |
| 65 | 32 | 1 | 3.125 | (79.4) | 1.375 | (34.9) | 2.113 | (53.7) | .875 | (22.2) | 1.250 | (31.8) | 20 |
| 66 | 32 | 1 | 4.125 | (104.8) | 1.375 | (34.9) | 2.113 | (53.7) | .875 | (22.2) | 1.250 | (31.8) | 20 |
| 67 | 32 | 1 | 3.125 | (79.4) | 1.500 | (38.1) | 2.363 | (60.0) | 1.000 | (25.4) | 1.375 | (34.9) | 24 |
| 68 | 32 | 1 | 4.125 | (104.8) | 1.500 | (38.1) | 2.363 | (60.0) | 1.000 | (25.4) | 1.375 | (34.9) | 24 |
| 69 | 32 | 1 | 3.125 | (79.4) | 1.781 | (45.2) | 2.770 | (70.4) | 1.250 | (31.8) | 1.625 | (41.3) | 28 |
| 70 | 32 | 1 | 4.125 | (104.8) | 1.781 | (45.2) | 2.770 | (70.4) | 1.250 | (31.8) | 1.625 | (41.3) | 28 |
| 71 | 36 | 1 | 4.125 | (104.8) | 1.375 | (34.9) | 2.113 | (53.7) | .875 | (22.2) | 1.250 | (31.8) | 20 |
| 72 | 36 | 1 | 5.125 | (130.2) | 1.375 | (34.9) | 2.113 | (53.7) | .875 | (22.2) | 1.250 | (31.8) | 20 |
| 73 | 36 | 1 | 4.125 | (104.8) | 1.500 | (38.1) | 2.363 | (60.0) | 1.000 | (25.4) | 1.375 | (34.9) | 24 |
| 74 | 36 | 1 | 5.125 | (130.2) | 1.500 | (38.1) | 2.363 | (60.0) | 1.000 | (25.4) | 1.375 | (34.9) | 24 |
| 75 | 36 | 1 | 4.125 | (104.8) | 1.781 | (45.2) | 2.770 | (70.4) | 1.250 | (31.8) | 1.625 | (41.3) | 28 |
| 76 | 36 | 1 | 5.125 | (130.2) | 1.781 | (45.2) | 2.770 | (70.4) | 1.250 | (31.8) | 1.625 | (41.3) | 28 |
| 77 | 36 | 2 | 5.000 | (127.0) | 1.830 | (46.5) | 3.020 | (76.7) | 1.437 | (36.5) | 1.875 | (47.6) | 32 |
| 78 | 36 | 2 | 6.000 | (152.4) | 1.830 | (46.5) | 3.020 | (76.7) | 1.437 | (36.5) | 1.875 | (47.6) | 32 |
| 79 | 40 | 1 | 4.125 | (104.8) | 1.375 | (34.9) | 2.113 | (53.7) | .875 | (22.2) | 1.250 | (31.8) | 20 |
| 80 | 40 | 1 | 5.125 | (130.2) | 1.375 | (34.9) | 2.113 | (53.7) | .875 | (22.2) | 1.250 | (31.8) | 20 |
| 81 | 40 | 1 | 4.125 | (104.8) | 1.500 | (38.1) | 2.363 | (60.0) | 1.000 | (25.4) | 1.375 | (34.9) | 24 |
| 82 | 40 | 1 | 5.125 | (130.2) | 1.500 | (38.1) | 2.363 | (60.0) | 1.000 | (25.4) | 1.375 | (34.9) | 24 |
| 83 | 40 | 1 | 4.125 | (104.8) | 1.781 | (45.2) | 2.770 | (70.4) | 1.250 | (31.8) | 1.625 | (41.3) | 28 |
| 84 | 40 | 1 | 5.125 | (130.2) | 1.781 | (45.2) | 2.770 | (70.4) | 1.250 | (31.8) | 1.625 | (41.3) | 28 |
| 85 | 40 | 1 | 4.125 | (104.8) | 1.830 | (46.5) | 3.020 | (76.7) | 1.437 | (36.5) | 1.875 | (47.6) | 32 |
| 86 | 40 | 1 | 5.125 | (130.2) | 1.830 | (46.5) | 3.020 | (76.7) | 1.437 | (36.5) | 1.875 | (47.6) | 32 |
| 87 | 44 | 1 | 4.125 | (104.8) | 1.375 | (34.9) | 2.113 | (53.7) | .875 | (22.2) | 1.250 | (31.8) | 20 |
| 88 | 44 | 1 | 5.125 | (130.2) | 1.375 | (34.9) | 2.113 | (53.7) | .875 | (22.2) | 1.250 | (31.8) | 20 |
| 89 | 44 | 1 | 4.125 | (104.8) | 1.500 | (38.1) | 2.363 | (60.0) | 1.000 | (25.4) | 1.375 | (34.9) | 24 |
| 90 | 44 | 1 | 5.125 | (130.2) | 1.500 | (38.1) | 2.363 | (60.0) | 1.000 | (25.4) | 1.375 | (34.9) | 24 |
| 91 | 44 | 1 | 4.125 | (104.8) | 1.781 | (45.2) | 2.770 | (70.4) | 1.250 | (31.8) | 1.625 | (41.3) | 28 |
| 92 | 44 | 1 | 5.125 | (130.2) | 1.781 | (45.2) | 2.770 | (70.4) | 1.250 | (31.8) | 1.625 | (41.3) | 28 |
| 93 | 44 | 1 | 4.125 | (104.8) | 1.830 | (46.5) | 3.020 | (76.7) | 1.437 | (36.5) | 1.875 | (47.6) | 32 |
| 94 | 44 | 1 | 5.125 | (130.2) | 1.830 | (46.5) | 3.020 | (76.7) | 1.437 | (36.5) | 1.875 | (47.6) | 32 |
| 95 | 48 | 1 | 4.125 | (104.8) | 1.375 | (34.9) | 2.113 | (53.7) | .875 | (22.2) | 1.250 | (31.8) | 20 |
| 96 | 48 | 1 | 5.125 | (130.2) | 1.375 | (34.9) | 2.113 | (53.7) | .875 | (22.2) | 1.250 | (31.8) | 20 |
| 97 | 48 | 1 | 4.125 | (104.8) | 1.500 | (38.1) | 2.363 | (60.0) | 1.000 | (25.4) | 1.375 | (34.9) | 24 |
| 98 | 48 | 1 | 5.125 | (130.2) | 1.500 | (38.1) | 2.363 | (60.0) | 1.000 | (25.4) | 1.375 | (34.9) | 24 |
| 99 | 48 | 1 | 4.125 | (104.8) | 1.781 | (45.2) | 2.770 | (70.4) | 1.250 | (31.8) | 1.625 | (41.3) | 28 |
| 100 | 48 | 1 | 5.125 | (130.2) | 1.781 | (45.2) | 2.770 | (70.4) | 1.250 | (31.8) | 1.625 | (41.3) | 28 |
| 101 | 48 | 1 | 4.125 | (104.8) | 1.830 | (46.5) | 3.020 | (76.7) | 1.437 | (36.5) | 1.875 | (47.6) | 32 |
| 102 | 48 | 1 | 5.125 | (130.2) | 1.830 | (46.5) | 3.020 | (76.7) | 1.437 | (36.5) | 1.875 | (47.6) | 32 |
| 103 | 61 | 1 | 3.125 | (79.4) | 1.059 | (26.9) | 1.551 | (39.4) | .500 | (12.7) | .750 | (19.1) | 12 |
| 104 | 61 | 1 | 4.125 | (104.8) | 1.059 | (26.9) | 1.551 | (39.4) | .500 | (12.7) | .750 | (19.1) | 12 |

Table continued on the next page.

**AS85049/11 and MS3437B
Environmental Backshells**



Environmental
Backshells

TABLE II (Continued)

| Dash No. | Shell Size | Style | E | | K | | L | | Cable Range | | M85049/42 | | |
|----------|------------|-------|-------|---------|-------|--------|-------|--------|-------------|--------|-----------|--------|----|
| | | | Max | | Ref. | | Max | | Min | Max | Ref | | |
| 105 | 61 | 1 | 3.125 | (79.4) | 1.156 | (29.4) | 1.770 | (45.0) | .625 | (15.9) | .937 | (23.8) | 16 |
| 106 | 61 | 1 | 4.125 | (104.8) | 1.156 | (29.4) | 1.770 | (45.0) | .625 | (15.9) | .937 | (23.8) | 16 |
| 107 | 61 | 2 | 3.875 | (98.4) | 1.375 | (34.9) | 2.113 | (53.7) | .875 | (22.2) | 1.250 | (31.8) | 20 |
| 108 | 61 | 2 | 4.875 | (123.8) | 1.375 | (34.9) | 2.113 | (53.7) | .875 | (22.2) | 1.250 | (31.8) | 20 |
| 109 | 61 | 2 | 3.875 | (98.4) | 1.500 | (38.1) | 2.363 | (60.0) | 1.000 | (25.4) | 1.375 | (34.9) | 24 |
| 110 | 61 | 2 | 4.875 | (123.8) | 1.500 | (38.1) | 2.363 | (60.0) | 1.000 | (25.4) | 1.375 | (34.9) | 24 |
| 111 | 12 | 1 | 2.125 | (54.0) | 1.027 | (26.1) | 1.332 | (33.8) | .350 | (8.9) | .500 | (12.7) | 10 |
| 112 | 16 | 1 | 2.125 | (54.0) | 1.027 | (26.1) | 1.145 | (29.1) | .250 | (6.4) | .437 | (11.1) | 6 |
| 113 | 16 | 1 | 3.125 | (79.4) | 1.027 | (26.1) | 1.145 | (29.1) | .250 | (6.4) | .437 | (11.1) | 6 |
| 114 | 12 | 1 | 2.125 | (54.0) | 1.027 | (26.1) | .957 | (24.3) | .125 | (3.2) | .312 | (7.9) | 4 |
| 115 | 12 | 1 | 3.125 | (79.4) | 1.027 | (26.1) | .957 | (24.3) | .125 | (3.2) | .312 | (7.9) | 4 |
| 116 | 14 | 1 | 2.125 | (54.0) | 1.027 | (26.1) | 1.145 | (29.1) | .250 | (6.4) | .437 | (11.1) | 6 |
| 117 | 14 | 1 | 3.125 | (79.4) | 1.027 | (26.1) | 1.145 | (29.1) | .250 | (6.4) | .437 | (11.1) | 6 |
| 118 | 16 | 1 | 2.125 | (54.0) | 1.027 | (26.1) | 1.332 | (33.8) | .350 | (8.9) | .625 | (15.9) | 10 |
| 119 | 16 | 1 | 3.125 | (79.4) | 1.027 | (26.1) | 1.332 | (33.8) | .350 | (8.9) | .625 | (15.9) | 10 |
| 120 | 18 | 1 | 2.125 | (54.0) | 1.027 | (26.1) | .957 | (24.3) | .125 | (3.2) | .312 | (7.9) | 4 |
| 121 | 18 | 1 | 3.125 | (79.4) | 1.027 | (26.1) | .957 | (24.3) | .125 | (3.2) | .312 | (7.9) | 4 |
| 122 | 18 | 1 | 2.125 | (54.0) | 1.027 | (26.1) | 1.145 | (29.1) | .250 | (6.4) | .437 | (11.1) | 6 |
| 123 | 18 | 1 | 3.125 | (79.4) | 1.027 | (26.1) | 1.145 | (29.1) | .250 | (6.4) | .437 | (11.1) | 6 |
| 124 | 20 | 1 | 3.125 | (79.4) | 1.027 | (26.1) | 1.145 | (29.1) | .250 | (6.4) | .437 | (11.1) | 6 |
| 125 | 20 | 1 | 4.125 | (104.8) | 1.027 | (26.1) | 1.145 | (29.1) | .250 | (6.4) | .437 | (11.1) | 6 |
| 126 | 22 | 1 | 3.125 | (79.4) | 1.027 | (26.1) | .957 | (24.3) | .125 | (3.2) | .312 | (7.9) | 4 |
| 127 | 22 | 1 | 4.125 | (104.8) | 1.027 | (26.1) | .957 | (24.3) | .125 | (3.2) | .312 | (7.9) | 4 |
| 128 | 22 | 1 | 3.125 | (79.4) | 1.027 | (26.1) | 1.145 | (29.1) | .250 | (6.4) | .437 | (11.1) | 6 |
| 129 | 22 | 1 | 4.125 | (104.8) | 1.027 | (26.1) | 1.145 | (29.1) | .250 | (6.4) | .437 | (11.1) | 6 |
| 130 | 24 | 1 | 3.125 | (79.4) | 1.027 | (26.1) | 1.332 | (33.8) | .350 | (8.9) | .625 | (15.9) | 10 |
| 131 | 24 | 1 | 4.125 | (104.8) | 1.027 | (26.1) | 1.332 | (33.8) | .350 | (8.9) | .625 | (15.9) | 10 |
| 132 | 36 | 1 | 4.125 | (104.8) | 1.059 | (26.9) | 1.551 | (39.4) | .500 | (12.7) | .750 | (19.1) | 12 |
| 133 | 36 | 1 | 5.125 | (130.2) | 1.059 | (26.9) | 1.551 | (39.4) | .500 | (12.7) | .750 | (19.1) | 12 |
| 134 | 40 | 1 | 4.125 | (104.8) | 1.059 | (26.9) | 1.551 | (39.4) | .500 | (12.7) | .750 | (19.1) | 12 |
| 135 | 40 | 1 | 5.125 | (130.2) | 1.059 | (26.9) | 1.551 | (39.4) | .500 | (12.7) | .750 | (19.1) | 12 |
| 136 | 10 | 1 | 2.125 | (54.0) | 1.027 | (26.1) | 1.145 | (29.1) | .250 | (6.4) | .375 | (9.5) | 6 |
| 137 | 10 | 1 | 3.125 | (79.4) | 1.027 | (26.1) | 1.145 | (29.1) | .250 | (6.4) | .375 | (9.5) | 6 |
| 138 | 12 | 1 | 2.125 | (54.0) | 1.027 | (26.1) | 1.332 | (33.8) | .350 | (8.9) | .500 | (12.7) | 10 |
| 139 | 12 | 1 | 3.125 | (79.4) | 1.027 | (26.1) | 1.332 | (33.8) | .350 | (8.9) | .500 | (12.7) | 10 |
| 140 | 20 | 1 | 3.125 | (79.4) | 1.156 | (29.4) | 1.770 | (45.0) | .625 | (15.9) | .904 | (23.0) | 16 |
| 141 | 20 | 1 | 4.125 | (104.8) | 1.156 | (29.4) | 1.770 | (45.0) | .625 | (15.9) | .904 | (23.0) | 16 |
| 142 | 22 | 1 | 3.125 | (79.4) | 1.375 | (34.9) | 2.113 | (53.7) | .875 | (22.2) | 1.029 | (26.1) | 20 |
| 143 | 22 | 1 | 4.125 | (104.8) | 1.375 | (34.9) | 2.113 | (53.7) | .875 | (22.2) | 1.029 | (26.1) | 20 |
| 144 | 24 | 1 | 3.125 | (79.4) | 1.375 | (34.9) | 2.113 | (53.7) | .875 | (22.2) | 1.144 | (29.1) | 20 |
| 145 | 24 | 1 | 4.125 | (104.8) | 1.375 | (34.9) | 2.113 | (53.7) | .875 | (22.2) | 1.144 | (29.1) | 20 |
| 146 | 36 | 1 | 4.125 | (104.8) | 1.830 | (46.5) | 3.020 | (76.7) | 1.437 | (36.5) | 1.840 | (46.7) | 32 |
| 147 | 36 | 1 | 5.125 | (130.2) | 1.830 | (46.5) | 3.020 | (76.7) | 1.437 | (36.5) | 1.840 | (46.7) | 32 |
| 148 | 36 | 1 | 4.125 | (104.8) | 1.156 | (29.4) | 1.770 | (45.0) | .625 | (15.9) | .937 | (23.8) | 16 |
| 149 | 36 | 1 | 5.125 | (130.2) | 1.156 | (29.4) | 1.770 | (45.0) | .625 | (15.9) | .937 | (23.8) | 16 |
| 150 | 14 | 1 | 2.125 | (54.0) | 1.027 | (26.1) | .957 | (24.3) | .125 | (3.2) | .312 | (7.9) | 4 |
| 151 | 14 | 1 | 3.125 | (79.4) | 1.027 | (26.1) | .957 | (24.3) | .125 | (3.2) | .312 | (7.9) | 4 |
| 152 | 16 | 1 | 2.125 | (54.0) | 1.027 | (26.1) | .957 | (24.3) | .125 | (3.2) | .312 | (7.9) | 4 |
| 153 | 16 | 1 | 3.125 | (79.4) | 1.027 | (26.1) | .957 | (24.3) | .125 | (3.2) | .312 | (7.9) | 4 |
| 154 | 44 | 1 | 4.125 | (104.8) | 1.156 | (29.4) | 1.770 | (45.0) | .625 | (15.9) | .937 | (23.8) | 16 |
| 155 | 44 | 1 | 5.125 | (130.2) | 1.156 | (29.4) | 1.770 | (45.0) | .625 | (15.9) | .937 | (23.8) | 16 |
| 156 | 40 | 1 | 4.125 | (104.8) | 1.156 | (29.4) | 1.770 | (45.0) | .625 | (15.9) | .937 | (23.8) | 16 |
| 157 | 40 | 1 | 5.125 | (130.2) | 1.156 | (29.4) | 1.770 | (45.0) | .625 | (15.9) | .937 | (23.8) | 16 |

Downloaded from Elcodis.com electronic components distributor