

This document was generated on 02/17/2011

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0743203000		
Status:	Active		
		al/Analog Visual Interface, PCB Receptacle, Panel Mount, .76µm (30µ") Gold (Au), Screw Hole, 4- 40 Thread, 29	
Documents:			"
Drawing (PDF)	<u>PS-74320-001 (PDF)</u>	Test Summary TS-74320-001 (PDF) RoHS Certificate of Compliance (PDF)	Series image - Reference only
Agency Certification ∪∟		E29179	EU RoHS ELV and RoHS Compliant
General Product Family Series Application		I/O Connectors <u>74320</u> Wire-to-Board	REACH SVHC Not Reviewed Low-Halogen Status Not Reviewed
Comments Component Type MolexKits		DDWG (Digital Display Working Group) Standard Receptacle Yes	Need more information on product environmental compliance?
Overview Product Name Type		<u>microcross_dvi</u> MicroCross™DVI N/A	Email <u>productcompliance@molex.com</u> For a multiple part number RoHS Certificate of Compliance, <u>click here</u>
Physical Boot Color Circuits (Loaded) Circuits (maximum)		N/A 29 29	Please visit the <u>Contact Us</u> section for any non-product compliance questions.
Color - Resin Durability (mating cyc Flammability Gender	cles max)	Natural 100 94V-0 Receptacle	Search Parts in this Series 74320Series
Keying to Mating Par Lock to Mating Part Material - Metal		Yes Yes Copper Alloy	Mates With 88744 , 74323
Material - Plating Material - Plating Ter Material - Plating Ter Number of Rows		Gold Tin 3	Use With 71781 Panel Mount Hex Screw Kit
Orientation PC Tail Length PCB Locator PCB Retention		Vertical 2.34mm (.092") Yes Yes	
Packaging Type Panel Mount Pitch - Mating Interfa	CP	Tray Yes 1.90mm (.075")	
Pitch - Termination Ir Plating min - Mating Plating min - Termina	nterface	1.90mm (.075') 0.762μm (30μ") 2.540μm (100μ")	
Polarized to Mating F Polarized to PCB Ports		Yes 1	
Surface Mount Comp Temperature Range Termination Interface	- Operating	, No -20°C to +85°C Through Hole	
Waterproof / Dustpro	5	No	

Wire Size AWG		N/A
Electrical Current - Maximum p Grounding to Panel Shield Type Shielded	per Contact	3A Yes Full Shield Yes
Voltage - Maximum Material Info		40V AC (RMS)
Reference - Drav Product Specification Sales Drawing Test Summary		PS-74320-001 SD-74320-002 TS-74320-001

This document was generated on 02/17/2011 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION