

This document was generated on 11/18/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0743201003
Status: Active

Overview: microcross_dvi

Description: MicroCross™ DVI-I Digital/Analog Visual Interface, PCB Receptacle, Through Hole,

Right Angle, 3.12mm (.123") P.C. Tail Length, 29 Circuits, Lead Free

Documents:

<u>Drawing (PDF)</u> <u>RoHS Certificate of Compliance (PDF)</u>

Product Specification PS-74320-001 (PDF)

Agency Certification

UL E29179

General

Product Family I/O Connectors
Series 74320
Application Wire-to-Board

Comments DDWG (Digital Display Working Group) Standard

Type N/A

Physical

Boot Color N/A Circuits (Loaded) 29 Circuits (maximum) 29 Color - Resin Natural Durability (mating cycles max) 100 Flammability 94V-0 Gender Receptacle Keying to Mating Part Yes Lock to Mating Part Material - Metal Copper Alloy Material - Plating Mating Gold

 Material - Plating Mating
 Gold

 Material - Plating Termination
 Tin

 Number of Rows
 3

 Orientation
 Right Angle

 PC Tail Length
 3.12mm (.123")

 PCB Locator
 Yes


PCB Locator Yes
PCB Retention Yes
Packaging Type Tray
Panel Mount Yes
Pitch Moting Interface 1,000

Pitch - Mating Interface1.90mm (.075")Pitch - Termination Interface1.90mm (.075")Plating min - Mating0.762μm (30μ")Plating min - Termination2.540μm (100μ")

Polarized to Mating Part
Yes
Polarized to PCB
Yes
Ports
1
Surface Mount Compatible (SMC)
No

Temperature Range - Operating -20°C to +85°C
Termination Interface: Style Through Hole

Waterproof / Dustproof No Wire Size AWG N/A



EU ROHS
ELV and ROHS
Compliant
REACH SVHC
Not Reviewed
Low-Halogen Status



Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
For a multiple part number RoHS Certificate of Compliance, click here

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

Search Parts in this Series

<u>74320</u>Series

Mates With 88744 , 74323

Use With

Hex Screw Kit 71781-0001 or 71781-0002

Electrical

Current - Maximum per Contact ЗА Grounding to Panel Yes Full Shield Shield Type Shielded Yes Voltage - Maximum 40V AC (RMS)

Material Info

Country of Origin CN, HK, MX, US

Reference - Drawing Numbers Packaging Specification PK-74320-010 Product Specification PS-74320-001 Sales Drawing SD-74320-001 Test Summary TS-74320-001

This document was generated on 11/18/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION