Switchcraft®

Previous Page | Return to Index | Next Page

3.5 MM HEAVY-DUTY STEREO PLUG



FEATURES AND BENEFITS

- One piece tip rod with flat for easy solderability.
- Compliments current line of 3.5 mm jacks.
- Insert molded plug finger.
- Heavy Duty cable clamp provides better strain relief for larger cables
- Longer cable clamp for easier plug assembly and more room for

solder connections

- Knurl on the back of handle provides ergonomic gripping surface to tighten plug
- Tubular insulator included to prevent solder joints from contacting handle
- Longer handle for improved gripping surface and easy plug withdrawal from jack
- Large solder terminal for easy solderability

MARKETS

- Audio
- Consumer electronic equipment
- Broadcast studios
- Home recording equipment
- Audio cable assembly manufacturers
- Instrumentation
- Test equipment

SPECIFICATIONS

Contact Resistance:<0.020 ohms

Dielectric Withstand Voltage: 250 VAC (min.)

Insulation Resistance @ 500 VDC: 2,000 megohms (min.)

Working Voltage: 250 VAC, 140 VDC

Current Carry @ Working Voltage: 4 AMPS Insert/Withdrawal Force: Typical 2.5/2 pounds

Temperature Range: 0° to 66° Centigrade (operating) Passed MIL-STD-

202F Method 107G (Thermal Shock), and Method 201 (Vibration)

Life: 5000 cycles

Maximum Cable Size: .250" dia.

Materials

Tip Rod: Copper alloy, tin, or gold-plated **Ring:** Copper alloy, nickel, or gold-plated **Sleeve:** Copper alloy, nickel, or gold-plated **Handle:** Copper alloy, nickel, or gold-plated

Cable Clamp: C.R.S., tin-plated


Solder Terminal: Copper alloy, tin-plated

Tubular Insulator: Clear plastic

ORDERING INFORMATION

1. Order by part number

2. Contact Switchcraft for more information



Previous Page | Return to Index | Next Page

| Switchcraft home |
About Us | Products | What's New | Search | Contact Us