

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0513870530](#)
Status: **Active**
Overview: [usb_otg_onthego](#)
Description: USB On-The-Go (OTG) Mini-B Receptacle, Right Angle, Short Body, SMT Solder Tails and Through Hole Shell Tabs, with Cover Tape, Reflow DIP Type, Lead-free

Documents:

[3D Model](#) [Product Specification PS-51387-003 \(PDF\)](#)
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

General

Product Family	I/O Connectors
Series	51387
Application	Wire-to-Board
Component Type	Receptacle
Overview	usb_otg_onthego
Product Name	USB OTG (On-The-Go)
Type	Mini-B


Physical

Boot Color	N/A
Circuits (Loaded)	5
Circuits (maximum)	5
Color - Resin	Black
Gender	Receptacle
Lock to Mating Part	Yes
Material - Metal	High Performance Alloy (HPA), Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Number of Rows	1
Orientation	Right Angle
PCB Locator	Yes
PCB Retention	Yes
Packaging Type	Embossed Tape on Reel
Panel Mount	No
Pitch - Mating Interface	0.80mm (.031")
Pitch - Termination Interface	0.80mm (.031")
Plating min - Mating	0.762µm (30µ")
Plating min - Termination	1.016µm (40µ")
Polarized to Mating Part	Yes
Polarized to PCB	Yes
Ports	1
Surface Mount Compatible (SMC)	Yes
Temperature Range - Operating	0°C to +50°C
Termination Interface: Style	Surface Mount
Waterproof / Dustproof	No
Wire Size AWG	N/A

Electrical

Current - Maximum per Contact	1A
Shield Type	Full Shield
Shielded	Yes
Voltage - Maximum	30V AC (RMS)/DC

Solder Process Data



EU RoHS

ELV and RoHS Compliant
REACH SVHC
 Not Reviewed
Low-Halogen Status
Low-Halogen

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
 For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

51387Series

Mates With

59204-9405

Duration at Max. Process Temperature (seconds)	3
Lead-free Process Capability	Reflow Capable (SMT only)
Max. Cycles at Max. Process Temperature	1
Process Temperature max. C	245

Material Info

Reference - Drawing Numbers

Packaging Specification	SPK-51387-001
Product Specification	PS-51387-003, RPS-51387-003, RPS-51387-005
Sales Drawing	SD-51387-005, SD-51387-006

This document was generated on 01/12/2011

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION