



USB-A-D-S-B-TH

USBR-A-S-F-O-TH



USB-AM-S-F-W-TH



USB-A-S-F-B-VU

USB-A, USBR-A, USB-AM SERIES

STANDARD & RUGGED USB INTERFACES


SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?USB-A or www.samtec.com?USBR-A

- Insulator Material:** High Temperature Thermoplastic
- Contact Material:** Phosphor Bronze
- Shell Material:** Copper Alloy
- Plating:** Gold on Contacts, Nickel on Shell, Tin on Tails
- Operating Temp Range:** -50°C to +85°C
- Current Rating:** 1 A per contact
- Voltage Rating:** 30 VAC
- Contact Resistance:** 30 mΩ max
- Cycles:** 1500 (maximum number of cycles tested)
- Packaging:** Packaged and shipped in Bulk Packaging Trays; Trays suitable for automation are available upon request.
- RoHS Compliant:** Yes
- Lead-Free Solderable:** -SM1=Yes, -TH & -VU=Yes (Wave Solder only)



TYPE	A	SHELL TYPE	PLATING	COLOR	TERMINATION
USB = Standard Connector		-S = Single -D = Double (-TH option only)	-S = 30µ" (0,76 µm) Gold on Mating Area, Tin on Tails -F = Gold Flash on Mating Area, Tin on Tails	-B = Black -W = White -O = Orange (USBR only)	-TH = Through-hole -SM1 = Offset Surface Mount -VU = Upright, Through-Hole



SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?USB-AM

- Insulator Material:** High Temperature Thermoplastic
- Contact Material:** Phosphor Bronze
- Shell Material:** Copper Alloy
- Plating:** Gold on Contacts, Nickel on Shell, Tin on Tails
- Operating Temp Range:** -50°C to +85°C
- Current Rating:** 1 A per contact
- Voltage Rating:** 30 VAC
- Contact Resistance:** 30 mΩ max
- Cycles:** 1500 (maximum number of cycles tested)
- Packaging:** Packaged and shipped in Bulk Packaging Trays; Trays suitable for automation are available upon request.
- RoHS Compliant:** Yes
- Lead-Free Solderable:** -SM1=Yes, -TH=Yes (Wave Solder only)



USB	TYPE	SHELL TYPE	PLATING	COLOR	TERMINATION
	-AM = A Type (Plug)	-S = Single	-S = 30µ" (0,76 µm) Gold on Mating Area, Tin on Tails -F = Gold Flash on Mating Area, Tin on Tails	-B = Black -W = White	-TH = Through-hole -SM1 = Surface Mount

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 SAMTEC SILICON VALLEY • Tel: 408-395-5900 SAMTEC SOUTHERN CALIFORNIA • Tel: 1-800-726-8329
 SAMTEC AMERICA LATINA COMERCIO EXTERIOR LTDA • Tel: (+55 31) 3786 3227 SAMTEC UNITED KINGDOM • Tel: 44 01236 739292 SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0
 SAMTEC FRANCE • Tel: 33 01 60 95 06 60 SAMTEC ITALY • Tel: 39 039 8890337 SAMTEC NORDIC/BALTIC • Tel: +46-84477280 SAMTEC BENELUX • Tel: 44 01236 739292 SAMTEC ISRAEL • Tel: 972-3-7526600
 SAMTEC INDIA • Tel: +91-80-3272 1612 SAMTEC ASIA PACIFIC • Tel: 65 6745-5955 SAMTEC JAPAN • Tel: 045-475-1385 SAMTEC CHINA • Tel: 86-21-61103766 SAMTEC TAIWAN • Tel: 886-2-2735-6109
 Downloaded from Elcodis.com electro SAMTEC HONG KONG • Tel: 852-2600-9858 SAMTEC KOREA • Tel: 82-31-717-5685 SAMTEC ANZ • Tel: 613 9512 7747 SAMTEC SOUTH AFRICA • Tel: 27 11 452 8112