

This document was generated on 11/16/2010

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0670689011		
			$\sim$
Status:	Active		
Overview:	<u>usb</u>		
Description:	Universal Serial Bus (USE	3), Shielded I/O, Type B Receptacle, Right Angle with Straight	
		m(30µ") Gold(Au) Plating, Tray Pack, Lead Free	
	· · ·		
Documents:			
3D Model		Product Specification PS-67998-0000 (PDF)	
		RoHS Certificate of Compliance (PDF)	
Drawing (PDF)		ROAS Certificate of Compliance (PDF)	Carries Corriso
			Series
Agency Certifica	ation		image - Reference only
CSA		LR19980	
UL		E29179	EU RoHS China RoHS
			ELV and RoHS
General			Compliant
Product Family		I/O Connectors	REACH SVHC
Series		67068	Not Reviewed
Application		Wire-to-Board	Low-Halogen Status
Comments		Single	Not Low-Halogen
		•	
Component Type		Receptacle	Need more information on product
Overview		<u>usb</u> USB	environmental compliance?
Product Name			
Туре		В	Email productcompliance@molex.com
Dhysical			For a multiple part number RoHS Certificate of
Physical			Compliance, <u>click here</u>
Boot Color		N/A	
Circuits (Loaded)		4	Please visit the Contact Us section for any
Circuits (maximum)		4	non-product compliance questions.
Flammability		94V-0	
Gender		Receptacle	
Lock to Mating Part		Yes	
Material - Plating Mating		Gold	Search Parts in this Series
Material - Plating Termination		Tin	<u>67068</u> Series
Number of Rows		2	
Orientation		Right Angle	Mates With
PC Tail Length		2.80mm (.110")	
PCB Locator		Yes	USB Type B Plug
PCB Retention		Yes	
PCB Thickness - Re	commended	1.60mm (.063")	
Packaging Type		Tray	
Panel Mount		No	
Pitch - Mating Interface		2.50mm (.098")	
Pitch - Termination Interface		2.50mm (.098")	
Plating min - Mating		0.762µm (30µ")	
Plating min - Termination		0.762μm (30μ.) 1.905μm (75μ")	
		Yes	
Polarized to Mating I	an		
Polarized to PCB		Yes	
Ports	notible (CMC)	1	
Surface Mount Com		Yes	
Temperature Range		0°C to +50°C	
Termination Interface		Through Hole	
Waterproof / Dustpro	oof	No	
Wire Size AWG		N/A	
<b></b> , , , ,			
Electrical			
Current - Maximum	per Contact	1.5A	

Shield Type	Full Shield
Shielded	Yes
Voltage - Maximum	30V (RMS)

## Material Info

**Reference - Drawing Numbers** Product Specification Sales Drawing

PS-67998-0000 SD-67068-003

## This document was generated on 11/16/2010 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION