


1734091-1 Product Details

Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



1734091-1

TE Part Number: 1734091-1

Active

Add to Part List

Universal Serial Bus (USB) Connectors

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Connector
- Size = Standard
- B Series
- Receptacle
- Without Locking Feature

[View all Features](#) | [Find Similar Products](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)
- [Request Samples](#)

NEW!

Documentation & Additional Information

Product Drawings:

- [USB CONN., RIGHT ANGLE, SHIELD, FLANGE, B TYPE](#) (TIF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Connector
- Size = Standard
- Gender = Receptacle
- Number of Ports = 1
- Orientation = Right Angle
- PCB Thickness (mm [in]) = 1.57 [0.062]
- Number of Positions = 4

Mechanical Attachment:

- Mount Location = Top

Electrical Characteristics:

- Panel Ground Type = M2 Threaded Hole

Termination Related Features:

- Termination Method = Solder to PC Board
- Tail Length (mm [in]) = 2.91 [0.115]

Body Related Features:

- [Series](#) = B
- Locking Feature = Without
- [Panel Ground](#) = With
- PCB Retention Method = Kinked Legs
- Shell Plating = Nickel over Copper
- Pick and Place Cover = Without
- Locating Posts = Without

Contact Related Features:

- Contact Termination Type = Through Hole
- [Contact Mating Area Plating Material](#) = Gold
- Contact Mating Area Plating Thickness = 30 Microinches

Housing Related Features:

- [Housing Color](#) = Black

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- Terminate To = Printed Circuit Board

Packaging Related Features:

- Panel Ground Location = Top
- [Packaging Method](#) = Tray

Other:

- Brand = AMP