



**MUSB, MUSBR, UUSB SERIES**

# MINI & MICRO USB 2.0 INTERFACES

**SPECIFICATIONS**

For complete specifications and recommended PCB layouts see [www.samtec.com?MUSB](http://www.samtec.com?MUSB) or [www.samtec.com?MUSBR](http://www.samtec.com?MUSBR)

**Insulator Material:** High Temperature Thermoplastic  
**Contact Material:** Phosphor Bronze  
**Shell Material:** Brass  
**Plating:** Gold on Mating Area, Nickel on Shell, Tin on Tails  
**Operating Temp Range:** -50°C to +85°C  
**Current Rating:** 1A per contact  
**Voltage Rating:** 30 VRMS  
**Contact Resistance:** 50 mΩ max  
**Minimum Cycles:** 1500  
**Packaging:** Packaged and shipped in Bulk Packaging Trays; Trays suitable for automation are available upon request.  
**RoHS Compliant:** Yes  
**Lead-Free Solderable:** Yes

TYPE	NO. OF CONTACTS	PLATING	COLOR	TYPE	SM	A
<b>MUSB</b> = Mini USB 2.0	<b>-05</b>	<b>-F</b> = Gold Flash on Mating Area, Tin on Tails <b>-S</b> = 30μ" (0,76μm) Gold on Mating Area, Tin on Tails	<b>-O</b> = Orange <b>-</b> = Leave blank for MUSB	<b>-B</b> = B Type (MUSB & MUSBR) <b>-AB</b> = AB Type (MUSB only) <b>-A</b> = A Type (MUSBR only)		

**ALSO AVAILABLE**  
Mini USB-A Type. Call Samtec.

High retention option

**SPECIFICATIONS**

For complete specifications and recommended PCB layouts see [www.samtec.com?UUSB](http://www.samtec.com?UUSB)

**Insulator Material:** Black LCP  
**Contact Material:** Phosphor Copper  
**Plating:** Au over 50μ" (1,27μm) Ni  
**Shield Plating:** Sn over 50μ" (1,27μm) Ni  
**Operating Temp Range:** -30°C to +80°C  
**Current Rating:** 1A (pin 2, 3, 4) per signal contact, 1.8A (pin 1, 5) per power contact  
**Voltage Rating:** 100 VAC  
**Contact Resistance:** 50 mΩ max  
**Cycles:** 10,000  
**RoHS Compliant:** Yes

UUSB	TYPE	S	PLATING	TERMINATION	TR
<b>UUSB</b> = Micro USB 2.0	<b>-AB</b> = Micro AB <b>-B</b> = Micro B		<b>-F</b> = Gold Flash on Mating Area and Tails <b>-S</b> = 30μ" (0,76 μm) Gold on Mating Area, Gold Flash on Tails	<b>-SM</b> = Surface Mount	<b>-TR</b> = Tape & Reel

Due to technical progress, all designs, specifications and components are subject to change without notice.

[WWW.SAMTEC.COM](http://WWW.SAMTEC.COM)