

1734181 -6 Product Details

Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



1734181 -6

[Active](#)

Universal Serial Bus (USB) Connectors

[Always EU RoHS/ELV Compliant](#) ([Statement of Compliance](#))

Product Highlights:

- ? USB Type = Standard
- ? A Series
- ? Receptacle
- ? 3 Ports
- ? Right Angle Mount Orientation

[View all Features](#) | [Find Similar Products](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- ? [RCPT. ASS'Y TRIPLE STACKED, USB, R/A, A TYPE.](#) (PDF, English)

Catalog Pages/Data Sheets:

- ? None Available

Product Specifications:

- ? None Available

Application Specifications:

- ? None Available

Instruction Sheets:

- ? None Available

CAD Files: ([CAD Format & Compression Information](#))

- ? [2D Drawing](#) (DXF, Version 0)
- ? [3D Model](#) (IGES, Version 0)
- ? [3D Model](#) (STEP, Version 0)

[List all Documents](#)

Additional Information:

- ? [Product Line Information](#)

Related Products:

- ? [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- ? Gender = Receptacle
- ? Number of Ports = 3
- ? [PCB Mount Style](#) = Thru Hole
- ? Mount = Flange Mount

Electrical Characteristics:

- ? Panel Ground Type = Spring Finger

Termination Related Features:

- ? Termination (Solder) Post Length (mm [in]) = 2.84 [0.112]

Body Related Features:

- ? [Series](#) = A
- ? Mount Orientation = Right Angle
- ? [Panel Ground](#) = With
- ? Shell Plating = Tin

Contact Related Features:

- ? [Contact Mating Area Plating Material](#) = Gold (30)
- ? Contact Material = Copper Alloy

Housing Related Features:

- ? [Housing Color](#) = Black
- ? Housing Material = Thermoplastic
- ? Housing Flammability Rating = UL 94V -0

Industry Standards:

- ? [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- ? [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- ? USB Type = Standard

Packaging Related Features:

- ? Panel Ground Location = Middle
- ? [Packaging Method](#) = Tray

Other:

- ? Brand = AMP