


**5788336 -1 Product Details**

**Live Product Chat** US Only  
8:30am - 5pm ET, Mon - Fri



**5788336 -1**

Active

**Universal Serial Bus (USB) Connectors**

[Always EU RoHS/ELV Compliant](#) ( [Statement of Compliance](#) )

**Product Highlights:**

- ? USB Type = Standard
- ? B Series
- ? Receptacle
- ? 1 Ports
- ? Vertical Mount Orientation

[View all Features](#) | [Find Similar Products](#)

**Quick Links**

- [Check Pricing & Availability](#)
- [Search for Tooling Product Feature Selector](#)
- [Contact Us About This Product](#)

**Documentation & Additional Information**

**Product Drawings:**

- ? [RECEPTACLE ASSY, 4 POSN.VERTICAL, THRU -HOLE, TYPE B,...](#) (PDF, English)

**Catalog Pages/Data Sheets:**

- ? None Available

**Product Specifications:**

- ? None Available

**Application Specifications:**

- ? None Available

**Instruction Sheets:**

- ? None Available

**CAD Files:** ( [CAD Format & Compression Information](#) )

- ? [2D Drawing](#) (DXF, Version O)
- ? [3D Model](#) (IGES, Version O)
- ? [3D Model](#) (STEP, Version O)

[List all Documents](#)

**Additional Information:**

- ? [Product Line Information](#)

**Related Products:**

- ? [Tooling](#)

**Product Features** (Please use the Product Drawing for all design activity)

**Product Type Features:**

- ? Gender = Receptacle
- ? Number of Ports = 1
- ? PCB Mount Style = Thru Hole
- ? PCB Thickness (mm [in]) = 1.57 [0.062]

**Termination Related Features:**

- ? Termination (Solder) Post Length (mm [in]) = 3.02 [0.119]

**Body Related Features:**

- ? [Series](#) = B
- ? Mount Orientation = Vertical
- ? [Panel Ground](#) = Without
- ? Shell Plating = Bright Tin

**Contact Related Features:**

- ? [Contact Mating Area Plating Material](#) = Gold Flash over Palladium Nickel or Gold (30) over Nickel
- ? Contact Material = Phosphor Bronze

**Housing Related Features:**

- ? [Housing Color](#) = Black
- ? Housing Material = Polyester
- ? Housing Flammability Rating = UL 94V -0

**Industry Standards:**

- ? [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- ? [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

**Conditions for Usage:**

- ? USB Type = Standard

**Packaging Related Features:**

- ? [Packaging Method](#) = Tray

**Other:**

- ? Brand = AMP