Home > Products > By Type > Backplane/Midplane > Product Feature Selector > Product Details

Product Details for 5536507



5536507

Active

2mm Centerline Futurebus+ Connectors

RoHS Compliant (Statement of Compliance)

Product Highlights:

-2

- Module Type = Signal
- 48 Signal Positions
- Free-Board (Receptacle)
- PCB Mount Angle = Right Angle
- Number of Rows = 4

View all Features

Quick Links

Check Pricing & Availability Search for Tooling View Mating Products (33) Product Feature Selector Contact Us About This Product

Documentation & Additional Information

Product Drawings:

RECEPTACLE ASSEMBLY, SIGNAL MODULE, Z -PACK, 2mm FB, (PDF, English)

Catalog Pages/Data Sheets:

? None Available

Product Specifications:

Connector, Z -PACK*, 2 mm FB, Signal and Power (PDF, English)

Application Specifications:

2 Z-PACK 2mm FB (Futurebus+) Receptacle and Pin Header... (PDF, English)

Instruction Sheets:

? None Available

CAD Files: (CAD Format & Compression Information

- ? 3D Model (STEP, Version O)
- ? 3D Model (IGES, Version O)
- 2 2D Drawing (DXF, Version O)

Additional Information:

Product Line Information

Additional Product Images:

? Line Drawing

Related Products:

- ? Tooling
- ? Mating Products (33)

List all Documents

Product Features

(Please use the Product Drawing for all design activity)

Product Type Features:

- ? Product Type = Free -Board (Receptacle)
- ? PCB Mount Angle = Right Angle
- ? Post Type = Solder Post

Mechanical Attachment:

? Module Type = Signal

Electrical Characteristics:

2 Voltage Rating (VAC) = 30

Termination Related Features:

Termination Post Length (mm [in]) = 2.73[0.107]

Body Related Features:

- ? Number of Signal Positions = 48
- ? Sequencing = No
- ? Number of Rows = 4
- ? Post Plating = Tin
- ? Centerline, Matrix (mm [in]) = 2.00 x 2.00 [.079 x .079]

Contact Related Features:

- ? Contact Material = Phosphor Bronze
- ? Contact Mating Area Plating = Gold (30)

Housing Related Features:

? Housing Material = Liquid Crystal Polymer (LCP)

Industry Standards:

- ? RoHS/ELV Compliance = RoHS compliant, ELV
- ? <u>Lead Free Solder Processes</u> = Wave solder capable to 240°C, Wave solder capable to 260° C, Wave solder capable to 265°C, Reflow solder capable to 245°C, Reflow solder capable to 260°C, Pin -in-Paste capable to 245°C, Pin in-Paste capable to 260°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

Other:

? Brand = AMP

Languages : English | Deutsch | Español | Português (do Brasil) | 2?????? | Italiano | 2??? (??) | 2? (??) | 2?? Country Sites : China | Japan