













Δ

4



This document is the property of and entabodies CONFIDENTIAL, and PROPRIETLEM, indirivations of FCI. Mo part of the information shown on this document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.

(8) AFTER INSERTION INTO CIRCUIT BOARD WITH OUALIFIED TOOL.

(9) THE PRODUCTS WHERE THE PART NUMBER ENDS IN LF MEET THE EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.

1/2

1|2

PRODUCT NUMBER

ALL PRODUCTS EXCEPT THOSE WITH PART NUMBERS CONTAINING (DRAWING NO.)-NI--- OR (DRAWING NO.)-N5---WILL WITHSTAND EXPOSURE TO 260°C FOR 60 SECONDS IN A CONVECTION, INFRA-RED OR VAPOR PHASE REFLOW OVEN. PART NUMBERS (DRAWING NO.)-NI--- AND (DRAWINGS NO.)-N5---WILL NOT WITHSTAND REFLOW AND AU CONTACT SURFACE OF THE CONTACTS SHALL BE EXPOSED TO A MAXIMIM 140°C FOR NO LONGER THAN 15 SECONDS IN A WAVE SOLDER APPLICATION.

(10) REFER TO 89007 FOR OTHER LOAD VARIATIONS.

mat 'I	tolerances unless otherwise specified					CUSTOMER				F	Sj										
ltr	ecn	n no. dr		do	date		0.X ±0.3				COPY			www.fciconnect.com							
T						0.XX ±0.13				projection		title METRAL SIGNAL HEADER									
						.XXX ±.051			2 MOD, 5 ROW PRESS-FIT												
					angles	0° ±2°			W 7		Z MOD, J NOW FRESS-FIT							1.1			
						dr	T.BRUNGARD		11/19/99		MM		product family METRAL code								
						engr	M.STRAWSER		11/19/99				size dwg no					213			
							M.STRAWSER		11/19/99		scale			85832					sheet		
						appd	M.STRAWSER		02/29/00		1:1		A	03032				8			
sh	sheet		on																		
inc	index		sheet																		
					Pro/E								cag	e code	2	22526			4		

3 |

PDM: Rev:T

STATUS: Released Printed: May 16, 2009

В