





Comment = Assembly lubricated with Bellcore approved lubricant; TR-NWT-001217 Issue 1, Sept 1992; Connector tested and qualified against Bellcore Quality Level III, Central Office Applications.

Mechanical Attachment: • Board Mount = Free Board

- Module Length (mm [in]) = 50.00 [1.968]

• Mating Polarization Type = Multi-Purpose Center

- <u>Crosstalk Version</u> = Standard AMP Standard Option Number = 1

Electrical Characteristics:

Termination Related Features:

- Interface Type = 2mm HM
- Termination End Plating = Tin over Nickel

Body Related Features: • Type = Type A

- Number of Rows = 5
- Number of Positions = 110 . Grounding Contact = Without
- Rows Loaded = A, B, C, E, D

- Contact Plating, Mating Area, Material = Gold (30)
- Contact Style = Short Tail
- Contact Base Material = Phosphor Bronze

Housing Related Features: Connector Style = Receptacle

- Housing Material = Polyester GF
- Housing Color = Gray
- UL Flammability Rating = UL 94V-0

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Not relevant for lead free process
- . RoHS/ELV Compliance History = Always was RoHS compliant

Packaging Related Features:

Packaging Quantity = 11

Other:
• Brand = AMP

🚨 BOOKMARK 📲 😭 🧦 ...)

Corporate Information **Quick Links** Customer Support Sign up for our eNewsletter Check Distributor Inventory Email or Chat with Us Who We Are Cross Reference Find a Phone Number Follow Us On: News Room Find Documents & Drawings Search Knowledge Base 🕒 🚮 🕶 in 👑 Supplier Portal Product Compliance Support Center Manage Your Account Careers Site Map Visit Us On: © 2010 Tyco Electronics All Rights Reserved | Privacy Policy Provide Website Feedback