
<u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>Two-Piece Connector</u> > <u>Product Feature Selector</u> > Product Details

Product Details for 5532436



5532436 -1

AMP - HDI (Four Beam) & TBC (Twin Beam) Connectors

RoHS Compliant (Statement of Compliance)

Product Highlights:

- ? Connector
- Plug
- Number of Positions = 100
- ? PCB Mount Style = Thru Hole
- ? PCB Mount Angle = Vertical

View all Features

Quick Links

Check Pricing &
Availability
Search for Tooling
Product Feature
Selector
Contact Us About
This Product

Documentation & Additional Information

Product Drawings:

ASSEMBLY, PIN, VERTICAL, HDI, LEAD -FREE, 4 ROW, WITH... (PDF, English)

Catalog Pages/Data Sheets:

? None Available

Product Specifications:

2 Connector, Interconnect, High Density (PDF, English)

Application Specifications:

? None Available

Instruction Sheets:

? None Available

CAD Files:

? None Available

Additional Information:

? Product Line Information

Related Products:

? Tooling

List all Documents

Product Features

(Please use the Product Drawing for all design activity)

Product Type Features:

- ? Product Type = Connector
- ? Gender = Plug
- ? Number of Positions = 100
- ? PCB Mount Style = Thru Hole
- ? PCB Mount Angle = Vertical
- ? Make First / Break Last = No
- ? <u>Mating Polarization</u> = Without? <u>Special PCB Retention</u> = Without

Termination Related Features:

- ? Termination Post Length (mm [in]) = 4.83 [0.190]
- ? Solder Tail Plating = Tin

Body Related Features:

- ? Number of Rows = 4
- ? Centerline (mm [in]) = 2.54 [0.100]

Contact Related Features:

- ? Contact Type = Four -Beam
- ? Contact Mating Area Plating = Gold (30)
- ? Contact Material = Phosphor Bronze
- ? Contact Underplating = Nickel

Housing Related Features:

- Property is a second of the second of the
- ? Housing Color = Brown
- ? Housing Material Temperature = High

Configuration Related Features:

? Center Guide = Without

Industry Standards:

- ? Government/Industry Qualification = No
- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260° C, Wave solder capable to 265°C, Reflow solder capable to 245°C, Reflow solder capable to 260°C, Pin -in-Paste capable to 245°C, Pin in-Paste capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Other:

? Brand = AMP