Our commitment. Your advantage.

Products

Documentation

esources My Account

Customer Support

Home > Products > By Type > Eurocard Connectors > Product Feature Selector > Product Details

5650959 - 5 Product Details



5650959 -5

✓ Active

Eurocard Type R

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- ? Receptacle
- ? Number of Positions = 150
- ? PCB Mount Angle = Right Angle
- ? Yes PCB Retention Feature
- ? Boardlock(s)

<u>View all Features</u> | <u>Find Similar</u> Products

Live Product Chat US Only 8:30am - 5pm ET, Mon - Fri

Quick Links

Check Pricing &
Availability
Search for Tooling
View Mating
Products (9)
Product Feature
Selector

Contact Us About
This Product

Documentation & Additional Information

Product Drawings:

ASSEMBLY, RECEPTACLE, EUROCARD, TYPE R, LEAD -FREE, 1... (PDF, English)

Catalog Pages/Data Sheets:

? None Available

Product Specifications:

? None Available

Application Specifications:

Eurocard Connectors Types B,C,M,Q,R, & Enchanced Typ... (PDF, English)

Instruction Sheets:

? None Available

CAD Files:

? None Available

Additional Information:

Product Line Information

Related Products:

- ? Tooling
- ? Mating Products (9)

List all Documents

Product Features

(Please use the Product Drawing for all design activity)

Product Type Features:

- ? Product Type = Receptacle
- ? Number of Positions = 150
- ? PCB Mount Angle = Right Angle
- ? PCB Retention Feature = Yes
- ? Post Type = Solder Post? Mating Polarization = Without
- ? Guides = Without
- ? Make First / Break Last = No
 ? DIN Level = II
- PCB Thickness (Minimum) (mm [in]) = 1.57 [0.062]
- ? Color = Gray

Termination Related Features:

- Termination (Solder) Post Length (mm [in]) = 2.79 [0.110]
- ? Solder Tail Contact Plating = Tin

Body Related Features:

- ? PCB Retention Method = Boardlock(s)
- ? Rows Loaded = A, B, C
- Contact Cross Section (mm [in]) = 0.30 x 0.61 [.012 x .024]

Contact Related Features:

- ? Contact Material = Copper Alloy
- Contact Mating Area Plating Material = DIN 41612 Class 2

Housing Related Features:

- ? Housing Material = Polymer
- ? Housing Flammability Rating = UL 94V -0

Industry Standards:

- ? Rohs/ELV Compliance = Rohs compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260° C, Wave solder capable to 265°C
- ? Flux Tight Coating = Without
- ? RoHS/ELV Compliance History = Always was RoHS compliant

Other:

? Brand = AMP

Provide Website Feedback | Contact Customer Support