Home > Products > By Type > Eurocard Connectors > Product Feature Selector > Product Details

#### 5650978 - 5 Product Details



5650978 -5

TE Part Number: 5650978 -5

✓ Active

Add to Part List

## **Eurocard Type C**

Always EU RoHS/ELV Compliant (Statement of Compliance)

### **Product Highlights:**

- ? Type C Connectors
- ? Plug
- ? Number of Positions = 32
- ? Rows Loaded = A, C
- ? Terminate To Printed Circuit Board

<u>View all Features</u> | <u>Find Similar</u> <u>Products</u> Live Product Chat US Only 8:30am - 5pm ET, Mon - Fri

#### Quick Links

Check Pricing &
Availability
Search for Tooling
View Mating
Products (11)
Product Feature
Selector
Contact Us About
This Product

### **Documentation & Additional Information**

# Product Drawings:

ASSEMBLY, PIN, EUROCARD, TYPE 1/C, A and C, 32/48 PO... (PDF, English)

#### Catalog Pages/Data Sheets:

None Available

## **Product Specifications:**

? None Available

### **Application Specifications:**

Eurocard Connectors Types B,C,M,Q,R, & Enchanced Typ... (PDF English)

#### Instruction Sheets:

? None Available

#### **CAD Files:**

? None Available

#### Additional Information:

Product Line Information

#### Related Products:

- ? Tooling
- ? Mating Products (11)

List all Documents

## **Product Features**

(Please use the Product Drawing for all design activity)

### **Product Type Features:**

- Product Type = Type C Connectors
- ? Gender = Plug
- ? Number of Positions = 32
- ? PCB Retention Feature = Yes
- ? PCB Mount Angle = Right Angle
- ? Post Type = Solder Post
- ? Size = Half
- ? Make First / Break Last = No
- ? DIN Level = II
- ? Mounting Ears = With
- ? Guides = Without
- ? Toolless (Flat Rock) = No
- ? Color = Gray

## Termination Related Features:

- 7 Termination (Solder) Post Length (mm [in]) = 2.65 [0.104]
- ? Solder Tail Contact Plating = Tin

#### **Body Related Features:**

- Rows Loaded = A, C
- ? PCB Retention Method = Boardlock(s)
- ? Contact Cross Section (mm [in]) = 0.64 [.025] Sq.

## **Contact Related Features:**

- ? Contact Material = Copper Alloy
- Contact Mating Area Plating Material = DIN 41612 Class 2

# Housing Related Features:

- ? Housing Material = Polymer
- ? Housing Flammability Rating = UL 94V -0

## **Industry Standards:**

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260° C, Wave solder capable to 265°C
- ? Flux Tight Coating = Without
- ? RoHS/ELV Compliance History = Always was RoHS compliant

## Conditions for Usage:

- ? Terminate To = Printed Circuit Board
- ? <u>High Temperature Housing</u> = No

#### Other:

? Brand = AMP

Provide Website Feedback | Contact Customer Support