tyco Electronics		Search By: ^N Part Number ^N Text Enter a complete or partial part number
Products Documer ome > Products > By Ty	ntation Resources My Account Customer pe > Backplane/Midplane > Product Feature Selector	
roduct Details f	or 5223004 - 4 2mm Centerline Futurebu	us+ Connectors
	RoHS Compliant_ (Statement of	
	Product Highlights: Produle Type = Signal	Search for Tooling View Mating Products (23)
5223004	•4 ? 120 Signal Positions ? Free-Board (Receptacle) ? PCB Mount Angle = Right A ? Number of Rows = 5	
	? NUMBER OF ROWS = 5	This Product

Documentation & Additional Information		
Product Drawings: Product Drawings: ASSEMBLY, RECEPTACLE, SIGNAL, RIGHT ANGL (PDF, English)		
Catalog Pages/Data Sheets: 2 None Available	Related Products: <u>Tooling</u> <u>Mating Products (23)</u> 	
Product Specifications: Connector, Z -PACK*, 2 mm FB, Signal and Power	(PDF, English)	
Application Specifications: [•] Z-PACK 2mm FB (Futurebus+) Receptacle and Pin F (PDF, English)	leader	
Instruction Sheets: ² None Available		
CAD Files: (CAD Format & Compression Information ? <u>3D Model</u> (STEP, Version O) ? <u>3D Model</u> (IGES, Version O) ? <u>2D Drawing</u> (DXF, Version O)	_) List all Documents	
Product Features (Please use the Product Drawing for all design activity)		
Product Type Features: [•] Product Type = Free -Board (Receptacle) [•] PCB Mount Angle = Right Angle [•] Post Type = Solder Post	Contact Related Features: ^o Contact Material = Phosphor Bronze ^o Contact Mating Area Plating = Gold (30)	
Mechanical Attachment: <u>Module Type</u> = Signal	Housing Related Features: Provide Housing Material = Liquid Crystal Polymer (LCP)	
Electrical Characteristics: • Voltage Rating (VAC) = 30 Termination Related Features:	Industry Standards: ? <u>RoHS/ELV Compliance</u> = RoHS compliant, ELV compliant ? Lead Free Solder Processes = Wave solder	
 <u>Termination Related Features.</u> <u>Termination Post Length (mm [in])</u> = 2.73 [0.107] 	capable to 240°C, Wave solder capable to 260° C, Wave solder capable to 265°C, Reflow solder capable to 245°C, Reflow solder capable to 260°C, Pin - in - Paste capable to 245°C, Pin	_
Body Related Features: <u>Number of Signal Positions</u> = 120 <u>Sequencing</u> = No <u>Number of Rows</u> = 5 	in -Paste capable to 260°C ? RoHS/ELV Compliance History = Always was RoHS compliant	-
 Post Plating = Tin Post Plating = Tin 	Other:	

- Other:
 - ? Brand = AMP

 Languages
 : English |
 Deutsch |
 Español |
 Português (do Brasil)
 2????? |
 Italiano |
 ???? (??) |
 ?? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ??? (??) |
 ?? (??) |
 ??? (??) |
 ?? (??) |
 ?? (??) |
 ?? (??) |
 ?? (??) |
 ?? (??) |
 ?? (??) |
 ?? (??) |
 ?? (??) |
 ?? (??) |
 ?? (??) |
 ?? (??) |
 ?? (??) |
 ?? (??) |
 ?? (??) |
 ?? (??) |
 ?? (??) |
 <th?? (??) |</th>

Home Customer Support Supplier Site Map Privacy Policy Browser Support © 2006 Tyco Electronics Corporation All Rights Reserved

? Centerline, Matrix (mm [in]) = 2.00 x 2.00 [.079 x .079]