tyco
Electronics

Sign In

Search By: Part Number   Text   Tips

[Enter a complete or partial part number...] Go

Products   **Documentation**   **Resources**   **My Account**   **Customer Support**   **About Us**

Home > Products > By Type > Eurocard Connectors > Product Feature Selector > Product Details

174717 - 2 Product Details

174717   -2

✔ Active

Eurocard Type C

Not ELV or RoHS Compliant   (Find RoHS Compliant Alternates)

Product Highlights:

- Type C Connectors
- Plug
- Number of Positions = 96
- Rows Loaded = A, B, C
- Terminate To Printed Circuit Board

View all Features

Quick Links

Check Pricing & Availability
Search for Tooling
Product Feature Selector
Contact Us About This Product

Documentation & Additional Information

Product Drawings:
- JAPANESE (PDF, English)

Catalog Pages/Data Sheets:
- None Available

Product Specifications:
- None Available

Application Specifications:
- None Available

Instruction Sheets:
- None Available

CAD Files:
- None Available

Additional Information:
- Product Line Information

Related Products:
- Tooling

List all Documents

Product Features   (Please use the Product Drawing for all design activity)

Product Type Features:
- Product Type   = Type C Connectors
- Gender   = Plug
- Number of Positions   = 96
- PCB Retention Feature   = Yes
- PCB Mount Angle   = Right Angle
- Post Type   = Solder Post
- Size   = Standard
- Make First / Break Last   = No
- Bus Type   = FUTUREBUS, MULTIBUS (II), NUBUS, VMEbus, VXIBus
- DIN Level   = II
- Mounting Ears   = With
- Toolless (Flat Rock) = No
- Color = Gray

Termination Related Features:
- Termination Post Length (mm [in])   = 3.00 [0.118]

Body Related Features:
- Rows Loaded   = A, B, C
- PCB Retention Method   = Boardlock(s)
- Contact Cross Section (mm [in])   = 0.64 [.025] Sq.

Contact Related Features:
- Contact Material = Brass

Housing Related Features:
- Housing Material = Thermoplastic Polyester

Industry Standards:
- RoHS/ELV Compliance   = Not ELV/RoHS compliant
- Lead Free Solder Processes   = Not suitable for lead free processing
- Flux - Tight Coating   = Without

Conditions for Usage:
- Terminate To   = Printed Circuit Board
- High Temperature Housing   = No

Other:
- Brand = AMP

Provide Website Feedback | Contact Customer Support

Home | Customer Support | Supplier | Site Map | Privacy Policy | Browser Support