



SuperChassis 942S-600 / 942S-600B

Products | Chassis | 4U | [SC942S-600 / SC942S-600B]



Alternate View




Side Handles Not Included
(Available with Optional Rail Kit)

Key Features

1. Triple Redundant 600W Power Supply
2. 10 x 3.5" SCA Ultra320/160 SCSI Hot swappable Drive Bays
3. 2 x 5.25" Peripheral Drive Bays
4. 1 x 5.25" Drive Bay For 3.5" 1.44MB Floppy Drive
5. 7x Full-height, Fulllength expansion slot
6. 3 x 120mm Hotswappable Fans
7. 1 x 120mm Rear exhaust Fan
8. 2 x Front USB Ports (optional)
9. Power Switch & 5 LED Indicators

Rear View



Available Colors

Beige

Black

Links & Resources

[Recommended Boards](#)

[Chassis Manual](#)

Specifications

Product SKUs	
CSE-942S-600	SuperChassis 942S-600 (Beige)
CSE-942S-600B	SuperChassis 942S-600B (Black)
Form Factor	
4U chassis support for max. motherboard size - 12" x 13" E-ATX	
Processor Support	
Dual Xeon® Processors	
Dimensions	
Height	7.0" (178mm)
Width	17.8" (452mm)
Depth	23.8" (605mm)
Gross Weight	69 lbs (31.4kg)
Available Colors	Beige, Black
Expansion Slots	
7x Full-height, Fulllength expansion slots	
Drive Bays	
Hot-swap	<ul style="list-style-type: none"> • 10x 3.5" SCA Ultra320/160 Hotswap Drives • 2x M35S Mobile Racks
Peripheral Bay(s)	<ul style="list-style-type: none"> • 2x 5.25" Peripheral Drive Bay • 1x 5.25" Bay For Floppy Drive
SCSI Backplane	
2x SCAM942 Ultra320/160 Backplanes in 2 Mobile Racks (with SAF-TE)	
Front Panel	
Buttons	<ul style="list-style-type: none"> • Power On/Off button • System Reset button • Power LED
LEDs	<ul style="list-style-type: none"> • Hard drive activity LED • 2x Network activity LEDs • System Overheat LED • Power Fail LED
Ports	2x USB Ports (optional)
System Cooling	
Fans	<ul style="list-style-type: none"> • 3x 120mm Hotswappable Fans • 1x 120mm Rear Exhaust Fan
System Monitoring	
Chassis intrusion switch	
Operating Environment (System)	
Operating Temperature Range	10 - 35°C (50° to 95° F)
Non-Operating Temperature Range	-40 - +70°C (-40° to 158° F)
Humidity Range	8 - 90% non-condensing
Non-Operating Humidity Range	5 - 95% non-condensing
Power Supply	
600W Triple-redundant AC power supply with PFC	
AC Voltage	100 - 240V, 50/60Hz, 12 Amp
DC Output	5V + 3.3V ? 200W
+5V	30.0 Amp
+5V standby	2.0 Amp
-5V	1.0 Amp
+12V	40.0 Amp
-12V	1.0 Amp
+3.3V	36.0 Amp
Regulatory (Power Supply)	
Power Safety / EMC	<ul style="list-style-type: none"> • USA - UL listed, FCC • Canada - CUL listed • Germany - TUV Certified • Europe/CE Mark • EN 60950/IEC 60950 Compliant

Components

Standard Parts List			
	Part Number	Qty	Description
SC942S-600 Chassis	CSE942S-600	1	4U Chassis (Beige)
	CSE942S-600B	1	4U Chassis (Black)
Cable(s)	CBL-0043	1	10' Two-drop SCSI Ultra320 Cable
	CBL-0028	1	30' Two-drop SCSI Ultra320 Cable
	CBL-0064	1	9" 3 to 3-Pin Fan Power Extension Cord
Fan(s)	FAN-0053	3	120mm Hotswappable Fan
	FAN-0054	1	120mm Rear Exhaust Fan
Mobile Rack	CSEM35S	2	SCSI Mobile Rack 3x 5.25" Openings to 5x 3.5" Drives
Power Supply	PWS-0044	1	SP602-TS 600W Triple Redundant Power Supply
Rear I/O	-	1	Dual LAN I/O Shield for 4U
SCA	CSEPT17	10	1" SCA drive tray
	CSESCA-016	2	SCAM942 with SAF-TE
Tray(s)	CSEPT36(B)OEM	2	5.25" Dummy Tray with Rail (B = Black)
Optional Parts List			
	Part Number	Qty	Description
Front USB Kit	CSEPT29(B)	-	2 Ports Front USB Kit
Heatsink / Retention	-	-	Please refer to our Thermal Components Matrix
Mobile Rack	CSEM35T1	-	SATA Mobile Rack 3x 5.25" Openings to 5x 3.5" Drives
	CSEM34S	-	SCSI Mobile Rack 3x 5.25" Openings to 4x Drives
	CSEM34T	-	SATA Mobile Rack 3x 5.25" Openings to 4x Drives
Mounting Rails	CSEPT26(B)	-	4U Chassis Rail Kit (Includes Side Handles)
Peripheral Drives	FPDSONY-F(B)	-	Sony 3.5" Floppy Drive (Beige, B = Black)
Power Supply Module(s)	PWS-0044(M)	-	SP302-TS Module for PWS0044
Rear I/O	-	-	Other I/O Shield for 4U / Tower Chassis