

This document was generated on 11/19/2010

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

	2 <mark>8500</mark> The-Go (OTG) Shielded I/O Cable Assembly, USB A-to-Mini B, USB 2.0, 52' ) Length, White	
Documents: Drawing (PDF)	RoHS Certificate of Compliance (PDF)	Series
General Product Family Series Connector to Connector Overview Product Name Physical Cable Length Circuits (Loaded) Color - Resin Gender Lock to Mating Part Material - Plating Mating Material - Plating Termination Material - Resin Packaging Type Pitch - Mating Interface Plating min - Mating	Cable Assemblies <u>88740</u> USB Type A-to-Mini-B <u>usb</u> USB 0.80m (2.62') 5 Black Male-Male Yes Gold Tin Polyester Bag 0.80mm (.031"), 2.50mm (.098") 0.762µm (30µ")	EU RoHS       China RoHS         ELV and RoHS       Compliant         REACH SVHC       Image: Compliant         Not Reviewed       Image: Compliant         Low-Halogen Status       Image: Compliant         Not Reviewed       Image: Compliant         Need more information on product environmental compliance?       Image: Compliance         Email productcompliance @molex.com       For a multiple part number RoHS Certificate or Compliance, click here         Please visit the Contact Us section for any non-product compliance questions.
Plating min - Termination Single Ended Termination Interface: Style Wire Insulation Diameter Wire Size AWG Wire/Cable Type	4.064µm (000)) No Through Hole N/A 28 Round	Search Parts in this Series 88740Series Mates With USB On-The-Go (OTG) Mini-B Receptacle
Electrical Current - Maximum per Contact Shielded Voltage - Maximum Material Info	1A Yes 30V	$\begin{array}{c} 54819, \ 48242, \ 500075, \ 67503. \ Universal\\ Serial Bus Shielded Receptacle Type\\ A \ 67329 \ 67226, \ 67230, \ 89485. \ 54366\\ Universal Serial Bus Shielded I/O\\ Receptacle\\ \end{array}$
Reference - Drawing Num Sales Drawing	Ders SD-887328500	

This document was generated on 11/19/2010 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION