



Search Results

Home > Products Overview > Search Results >

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

Current refinements (click to remove) Search Tips Within Results

Text Search: 'F5D6P-NM1Y'

Your search criteria matched only one product, shown below

F5D6P-NM1Y



- Pass all TIA/EIA-568-B.3 performance requirements
- Insertion loss per connection: 0.10dB typical; 0.30dB maximum
- Factory terminated and 100% tested for insertion loss
- Insertion loss data recorded for every multimode patch cord
- Lifetime traceability of test data to a Q.C. number on each patch cord
- SC Duplex Patch Cords include SC Duplex Clips to maintain polarity
- Highest quality flame retardant fiber optic cable with tight -buffered coating on each optical fiber

| | |
|------------------------------|---|
| Part Number | F5D6PNM1Y |
| RoHS Compliancy Status | Compliant |
| Note | F5D6PNM1Y replaces F5D6PNM1 |
| Part Description | FJ® Plug to pigtail multimode duplex patch cord (one ® Plug on one end and open on the other end) - 50/125µm. |
| Product Type | FJ® Patch Cords |
| Length (m) | 1 |
| Fiber Compatibility | 50/125µm |
| Fiber Cable Size | 3mm |
| Fiber Cable Type | Jacketed |
| Fiber Type | Multimode |
| Connector 1 Type | FJ® Plug |
| Connector 2 Type | Pigtail |
| End Configurations | FJ® Plug to Pigtail |
| Fiber Count | 2 |
| Flammability Rating | Riser (OFNR) |
| Pricing Description | PC FJ Plug To Pigtail 50m 1m |
| Min. Order UOM | PC |
| Min. Order Qty. | 1 |
| BOM Qty. (# of Pkgs.) | <input type="text" value="0"/> |
| Add to Favorite Product List | |

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.