



(2,00mm) .0787"
TCSD SERIES







TIGER EYE™ IDC SOCKET CABLE

Mates with: TMM, TMMH, STMM, MMT, TW, MTMM, EHT, ETMM (-SR), ZSTMM

FEATURES

- Low profile, only 5mm (.200") assembled height
- Four-finger contacts optimize normal, insertion and withdrawal forces
- Ask about our custom IDC design capabilities

SPECIFICATIONS

For complete specifications see www.samtec.com?TCSD

Insulator Material: Black Glass Filled Polyester Contact:

BeCu Plating:

Au or Sn over 50μ" (1,27μm) Ni Wire:

28 AWG 7/36 Stranded, Tinned, Copper with Gray PVC Insulator Current Rating:

Operating Temp Range: -40°C to +105°C

Lead Size Accepted: $(0.48\text{mm}) \cdot 0.19$ " to $(0.53\text{mm}) \cdot 0.21$ " Contact Resistance: $15 \text{ m}\Omega$ maximum delta from initial Insertion Depth: $(2.87\text{mm}) \cdot 1.13$ " to $(3.17\text{mm}) \cdot 1.25$ " Insertion Force: $(\text{Single contact only}) \cdot 2 \text{ oz. } (0.56\text{N})$ average

Vithdrawal Force: (Single contact only) 1.4 oz (0,39N) average RoHS Compliant:

POLARIZING

Specify PK-01-07 for polarizing key (Available in wheels of six each). Also polarizes SMM Series socket strips.

KEY

Note: Other Gold plating options available. Contact Samtec.

Note: TCSD Series assemblies are non-standard, non-returnable.

