

4

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

SIMPLEX FIBER OPTIC SC TO LC PATCH CORD CABLE SC CONNECTOR LC CONNECTOR										
PANDU I T		SC	CONNECT	OR	LC CONNECTOR					
PART NO.	RATING	FIBER TYPE	COUNT	COLOR	MAX. IL	RL	COLOR	MAX. IL	RL	COLOR
FXF3-10M*Y		10GbE 50/125um 0M3		AQUA	0.30dB	26dB	ELECTRIC IVORY	0.30dB	26dB	ELECTRIC IVORY
F6F3-10M*Y	RISER (OFNR)	62.5/125um OMI	SIMPLEX 1.6mm	ORANGE	0.30dB	20dB	ELECTRIC I VORY	0.30dB	20dB	ELECTRIC IVORY
F9F3-10M*Y		9/125um 051		YELLOW	0.75dB	55dB	BLUE	0.35dB	55dB	BLUE

* - DENOTES PATCH CORD LENGTH, WHERE M = METERS AND F = FEET

										SI	SIMPLEX FIBER OPTIC PATCH CORD SC TO LC CONFIGURATION customer drawing			
										THIRD ANGLE PROJECTION	UNLESS OTHERWISE SPECIFIED. DIMENSIONAL TOLERANCES ARE: (.XX) (.XXX):.010 [0.3] (.XX):.03 [0.8] ANGLES	DRAWING FILENAME M02779CH_DC_00A.prt SCALE NONE		
										DRAWN BY MC	REVIEW DRAWING NUMBERS	PART NO. SEE TABLE		
R	06-05-07	мс		RELEASED TO PRODUCTION	02779-38					05-23-07		DRAWING NO. SIZE 02779-38		
REV	DATE	BY	СНК	DESCRIPTION	ECN -	R	CUST	SUP	отн	CHK *D		(SHT. 2 of 2)		