



### FEATURES:

- The molded strain relief is tightly bonded to the cable jacket for superior strength and durability.
- Gold plated center contacts assure the most noise free connection possible.
- The connectors and cable are selected for the best performance possible.
- Teflon insulation and tarnish resistance outer shells provide the longest lifetime of any cable assembly available.
- For use below 50 VDC (75 VAC) when hand contact is possible.
- Maximum useful voltage is 500 V.

### MATERIALS:

BNC Connector: Body – Brass, Nickel Plated

Center Conductor – Brass, Gold Plated

Impedance: 50 Ohms

UHF Connector: Body – Brass, Nickel Plated

Center Conductor – Brass, Gold Plated

Impedance: Non-Constant

Strain Relief Boot: PVC, Color - Black

Cable: RG58C/U, 50 Ohm impedance, .195 (4,95mm) O.D. Marking: "POMONA 1367-C-XX"

### RATINGS:

Operating Voltage: 500 VRMS

Operating Temperature: +50°C (+122°F) Max.

### ORDERING INFORMATION: Model 1367-C-XX

XX = Length in inches. Std. Lengths: 60" (152.40cm). Additional lengths can be ordered upon request.

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA