

443068 - 1 Product Details

Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



LGH Single - Pin Connectors and Cable Assemblies

[Always EU RoHS/ELV Compliant](#) ([Statement of Compliance](#))

Product Highlights:

- ? Lead Assembly
- ? 40 kVDC Operating Voltage
- ? Lead Assembly Type = Double -End
- ? Assembly Length = 838.20 mm
- ? Barrel Depth = 45.97 mm

[View all Features](#) | [Find Similar Products](#)

443068 - 1

[Active](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- ? [LEAD ASSY, POS STOP, DBL ENDLGH -3 \(NO CAP\)](#) (PDF, English)

Catalog Pages/Data Sheets:

- ? None Available

Product Specifications:

- ? [Standard LGH Connectors, Series 1/2I, 1/2LI, 1I, 1LI...](#) (PDF, English)

Application Specifications:

- ? None Available

Instruction Sheets:

- ? None Available

CAD Files:

- ? None Available

Additional Information:

- ? [Product Line Information](#)

Related Products:

- ? [Tooling](#)

[List all Documents](#)

Product Features

(Please use the Product Drawing for all design activity)

Product Type Features:

- ? [Product Type](#) = Lead Assembly
- ? [Mount Angle](#) = Straight
- ? [Shielded](#) = No
- ? Wire Size (mm² [AWG]) = 16

Electrical Characteristics:

- ? [Operating Voltage \(kVDC\)](#) = 40

Body Related Features:

- ? [Lead Assembly Type](#) = Double -End
- ? [Assembly Length \(mm \[in\]\)](#) = 838.20 [33.000]
- ? [Barrel Depth \(mm \[in\]\)](#) = 45.97 [1.810]
- ? [Positive Stop Ferrule](#) = With
- ? Wire Color = White (Standard)
- ? Wire Diameter (mm [in]) = 6.98 [0.275]
- ? Wire Insulation = Silicone

Industry Standards:

- ? [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- ? [Lead Free Solder Processes](#) = Not relevant for lead free process
- ? RoHS/ELV Compliance History = Always was RoHS compliant

Other:

- ? Brand = AMP