

RF316-07SP1-07BJ1-0200

RF174-01RP1-02RP1-0300

**RF174, RF316 SERIES**

# 50Ω RG 174 & RG 316 CABLE ASSEMBLIES

**SPECIFICATIONS**

For complete specifications see [www.samtec.com?RF174](http://www.samtec.com?RF174) or [www.samtec.com?RF316](http://www.samtec.com?RF316)

**RF Connector:**

**Outer Contact Material:**  
Ni plated Brass (BNC)  
Au plated Brass (SMB & SMA)  
Au plated BeCu (MCX & MMCX)  
**Center Contact Material:**  
Au plated Brass (BNC-P, MCX-P, MMCX-P, SMA-P)  
Au plated BeCu (SMB-P)  
Au plated Phosphor Bronze (BNC-J)  
Au plated BeCu (SMA-J)  
**Insulator Material:** PTFE  
**Operating Temperature:**  
RF174: -50°C to +90°C  
RF316: -50°C to +165°C  
**Insulator Resistance:**  
5,000 MΩ  
**Impedance:** 50Ω  
**Frequency Range:** 0-6 GHz  
**RoHS Compliant:** Yes

**RG 174 Cable:**

**Impedance:** 50Ω  
**Capacitance:** 101.024pF/meter  
**Propagation Delay:**  
5.06 nsec/meter  
**Max Attenuation:**  
1.4dB @ 1GHz for 1 meter  
**Conductor Size:**  
26 AWG, (0,48mm) .019" dia.  
**Conductor Material:** Copper  
**Conductor Resistance:**  
0.14Ω/meter  
**Current Rating:** 5A DC  
**Insulator Material:** PE  
**Dielectric Constant:** 2.3dK  
**Shield Material:** Tin Copper  
**Jacket Material:** PVC  
**Jacket Diameter:**  
(2,70mm) .106"  
**Jacket Temp Rating:**  
-50°C to +90°C  
**Jacket Color:** Black  
**RoHS Compliant:** Yes

**RG 316 Cable:**

**Impedance:** 50Ω  
**Capacitance:** 96.432pF/meter  
**Propagation Delay:**  
4.83 nsec/meter  
**Max Attenuation:**  
1.25dB @ 1GHz for 1 meter  
**Conductor Size:**  
26 AWG, (0,51mm) .020" dia.  
**Conductor Material:**  
Silver Plated Copper  
**Conductor Resistance:**  
0.13Ω/meter max  
**Current Rating:** 5A DC  
**Insulator Material:** PTFE  
**Dielectric Constant:** 2.1dK  
**Shield Material:**  
Silver Plated Copper Clad Steel  
**Jacket Material:** FEP  
**Jacket Diameter:**  
(2,54mm) .100"  
**Jacket Temp Rating:**  
-50°C to +165°C  
**Jacket Color:** Amber  
**RoHS Compliant:** Yes

**Mates with:**  
MCX, MMCX,  
SMA, SMB5



Standard performance 26 AWG  
RG 174 coax cable

2.3dK

Plugs and  
Jacks

Single or  
Double Ended

**RF Cable  
Builder**

Quickly...Build a cable.  
Verify a part number.  
View print, Request price,  
Order sample...all online!

[www.samtec.com/rfbuilder](http://www.samtec.com/rfbuilder)

Straight or  
Right Angle



**CABLE TYPE**

**END 1  
CONNECTOR**

**END 2  
CONNECTOR**

Specify  
END OPTIONS  
from chart

**RF174**  
= RG 174 Cable

**RF316**  
= RG 316 Cable

| END OPTIONS  |  |
|--|--|
| -01SP1 = SMA, Straight Plug (30µ" (0,76µm) Gold on Center Contact, Gold Flash on Shell)    |  |
| -01RP1 = SMA, Right Angle Plug (30µ" (0,76µm) Gold on Center Contact, Gold Flash on Shell) |  |
| -07SP1 = SMB, Straight Plug (30µ" (0,76µm) Gold on Center Contact, Gold Flash on Shell)    |  |
| -07RP1 = SMB, Right Angle Plug (30µ" (0,76µm) Gold on Center Contact, Gold Flash on Shell) |  |
| -02SJ1 = MCX, Straight Jack (30µ" (0,76µm) Gold on Contact, Gold Flash on Shell)           |  |

| END OPTIONS   |  |
|---|--|
| -02RP1 = MCX, Right Angle Plug (30µ" (0,76µm) Gold on Center Contact, Gold Flash on Shell)  |  |
| -02SP1 = MCX, Straight Plug (30µ" (0,76µm) Gold on Center Contact, Gold Flash on Shell)     |  |
| -03SP1 = MMCX, Straight Plug (30µ" (0,76µm) Gold on Center Contact, Gold Flash on Shell)    |  |
| -03RP1 = MMCX, Right Angle Plug (30µ" (0,76µm) Gold on Center Contact, Gold Flash on Shell) |  |
| -04SP3 = BNC, Straight Plug (10µ" (0,25µm) Gold on Center Contact, Nickel on Shell)         |  |
| -05SP3 = TNC, Straight Plug (10µ" (0,25µm) Gold on Center Contact, Nickel on Shell)         |  |

Due to technical progress, all designs, specifications and components are subject to change without notice.

[WWW.SAMTEC.COM](http://WWW.SAMTEC.COM)



High performance 26 AWG  
RG 316 coax cable

2.1dK

Standard heat  
shrink wraps

Heavy Gold  
plated

Choice of RF  
connector styles

### ALSO AVAILABLE

- Connector Kits.
  - Additional plating options available.
  - Additional end connector combinations.
  - Knurled nuts with BNC option.
- Call Samtec.

Choice of RG 174 &  
RG 316 cable

Single or  
double ended

Variety of  
Bulkhead Jacks

## OVERALL LENGTH

—“XXXX”

= Overall Length in millimeters —0100 (100mm) minimum  
(Cable lengths larger than 1000 millimeters are not supported by S.I. Test data)

### STRIPPED & TINNED (Dimensions in mm)

| CALLOUT | A   | B   | C   |
|---------|-----|-----|-----|
| -303030 | 3.0 | 3.0 | 3.0 |
| -303040 | 3.0 | 3.0 | 4.0 |
| -403030 | 4.0 | 3.0 | 3.0 |
| -403040 | 4.0 | 3.0 | 4.0 |
| -404040 | 4.0 | 4.0 | 4.0 |

Both center conductor and braid shield are Stripped and Tinned.  
Call Samtec for other sizes.

### END OPTIONS

|   |  |
|---|--|
| -07BJ1 = SMB, Bulkhead Jack (30µ" (0,76µm) Gold on Center Contact, Gold Flash on Shell)                             |  |
| -01BJ1 = SMA, Straight Bulkhead Jack  |  |
| -01BR1 = SMA, Straight Bulkhead Jack, Reversed Polarity (30µ" (0,76µm) Gold on Center Contact, Gold Flash on Shell) |  |

### END OPTIONS

|  |  |
|--|--|
| -SING = Single-Ended (End 2 only)          |  |
| XXXXXX = Stripped & Tinned (End 2 callout) |  |

### END OPTIONS

|  |  |
|--|--|
| -04BJ3 = BNC, Bulkhead Jack (10µ" (0,25µm) Gold on Center Contact, Nickel on Shell)    |  |
| -05BJ3 = TNC, Bulkhead Jack (10µ" (0,25µm) Gold on Center Contact, Nickel on Shell)    |  |
| -06BJ2 = N Type, Bulkhead Jack (30µ" (0,76µm) Gold on Center Contact, Nickel on Shell) |  |

Due to technical progress, all designs, specifications and components are subject to change without notice.

[WWW.SAMTEC.COM](http://WWW.SAMTEC.COM)

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 SAMTEC SILICON VALLEY • Tel: 408-395-5900 SAMTEC SOUTHERN CALIFORNIA • Tel: 1-800-726-8329  
 SAMTEC AMERICA LATINA COMERCIO EXTERIOR LTDA • Tel: (+55 31) 3786 3227 SAMTEC UNITED KINGDOM • Tel: 44 01236 739292 SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0  
 SAMTEC FRANCE • Tel: 33 01 60 95 06 60 SAMTEC ITALY • Tel: 39 039 8890337 SAMTEC NORDIC/BALTIC • Tel: +46-84477280 SAMTEC BENELUX • Tel: 44 01236 739292 SAMTEC ISRAEL • Tel: 972-3-7526600  
 SAMTEC INDIA • Tel: +91-80-3272 1612 SAMTEC ASIA PACIFIC • Tel: 65 6745-5955 SAMTEC JAPAN • Tel: 045-475-1385 SAMTEC CHINA • Tel: 86-21-61103766 SAMTEC TAIWAN • Tel: 886-2-2735-6109  
 SAMTEC HONG KONG • Tel: 852-2600-9858 SAMTEC KOREA • Tel: 82-31-717-5685 SAMTEC ANZ • Tel: 613 9512 7747 SAMTEC SOUTH AFRICA • Tel: 27 11 452 8112