
Home > Products > By Type > Card Edge > Product Feature Selector > Product Details

Product Details for 5145169

- 4



PCI & PCI Express Connectors

RoHS Compliant (Statement of Compliance)

Product Highlights:

- ? Housing Color = White
- 92 Dual Positions
- 1.27 mm Centerline
- Bus Width = 64 Bit
- ? Voltage = 5 VAC
- View all Features

Active

Quick Links

Check Pricing &
Availability
Search for Tooling
Product Feature
Selector
Contact Us About
This Product

Documentation & Additional Information

Product Drawings:

CONNECTOR ASSEMBLY, 92 DUAL POSITION, .050 SERIES, S... (PDF, English)

Catalog Pages/Data Sheets:

? None Available

Product Specifications:

? Connector, Card Edge, .050 Centerline (PDF, English)

Application Specifications:

· Card Edge PC Board Connectors (PDF, English)

Instruction Sheets:

? None Available

CAD Files:

? None Available

Additional Information:

? Product Line Information

Related Products:

? Tooling

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- ? Number of Dual Positions = 92
- ? PCB Mount Style = Thru Hole
- ? Holddown Material = Brass
- ? Comment = Supplied with either cored or solid side walls.; Connector features one key at position 11.

Mechanical Attachment:

? Holddown Plating = Tin over Nickel

Electrical Characteristics:

? Voltage (VAC) = 5

Termination Related Features:

- ? Termination Post Length (mm [in]) = 2.54 [0.100]
- ? Solder Tail Plating = Tin

Body Related Features:

- ? Centerline (mm [in]) = 1.27 [0.050]
- Pus Width = 64 Bit
- ? PCB Retention Method = Holddown
- ? Ejector = Without
- ? Number of Holddowns = 3

Contact Related Features:

List all Documents

- ? Contact Mating Area Plating = Gold (30)
- ? Contact Material = Phosphor Bronze

Housing Related Features:

- ? Housing Color = White
- ? Housing Material = Thermoplastic

Industry Standards:

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260° C, Wave solder capable to 265°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

Other:

? Brand = AMP