



Cannon VEAM BIW

Home | Sign In | Site Map | Contact Us

SEARCH



Home > Search Tools > Part Number

## Part Number Search

You Searched For:

**Note:** Data provided here are offered in good faith and are as reliable and accurate as possible. However, they do not form part of any contract of supply or purchase unless specifically confirmed in writing by an authorized representative of ITT. All information and images shown are the property of ITT ICS and are not to be reproduced in any form without direct authorization from ITT ICS.  
 ITT ICS strongly recommends that you contact your local ITT Sales Office for confirmation of all the details you obtain through these Web pages. Please be aware that data may change at any time and without notice. For a listing of Sales Offices, local sales support, and authorized distributors please use the "Global Sales Locator" located either to the right of this data or at the top of every page.

- 
- 
- 
- 
- 

Our Catalog Part Number: DE-9P  
 Our Global Manufacturing Part Number: 112043-0000  
 Brand: Cannon Product Category: D Sub Product Line: D Sub Series: ORIGINAL D



**NO** RoHS compliant = material restrictions of lead, cadmium, hexavalent chromium, mercury, poly bromated biphenyl ether (PBB) and poly bromide diphenyl ether (PBDE) according to directive 2002/95/EC  
**NO** RoHS compatible = Compatible with lead free soldering process

### Export Compliance



Country of Compliance: United States  
 Commercial Shipments "C"  
 Export Compliance Notes: Controlled by the US Department of Commerce.

### Product Datasheet

General	Standard D-Subminiature
Wire Gauge Range AWG	AWG 20-28
Mating Cycles	50
Dielectric Withstanding Voltage	1200 VAC at sea level
Current Rating	7.5 A at 85°C / 5 A at 105°C
Contact Resistance	10 milli Ohm max
Operating Temperature	-55°/+125°
Salt Spray Test	20 hours
Shell Material	steel
Shell Finish	yellow chromate over cadmium or zinc
Insulator Material	Thermoplastic, type PCT UL 94V-0
Insulator Color	black
Contact Arrangement	9 contacts size 20
Gender	Pin
Contact Type	turned
Contact Material	copper alloy
Contact Finish	gold flash (Performance Class 3)
Contact Termination	Solder Pot
Mounting Methode	.120" (3,05mm) Through Hole



Home | About ITT | Products | Design Center | Literature | News & Events | Search Tools | Global Sales Support

[Channel Partners Sign-In](#)

Legal Disclaimer | Privacy Policy | Terms & Conditions | Provide Website Feedback

© 2011 ITT Corporation. All rights reserved.