


(1,27mm) .050" FFSD, FFMD SERIES





## TIGER EYE™ FLAT IDC WIRE CABLES

## **SPECIFICATIONS**

Mates with: FTS. FTSH. EHF. SHF, ESHF

For complete specifications see www.samtec.com?FFSD

**FFSD** 

Insulator Material:

Contact: BeCu

Plating: 10μ" (0,25μm) Au over 50μ" (1,27μm) Ni on contact area; Sn over 50μ' (1,27μm) Ni on balance

Wire: 30 AWG **Current Rating:** 

Operating Temp Range: -40°C to +105°C Lead Size Accepted: (0,41mm) .016" SQ Contact Resistance: 15 mΩ maximum delta from initial

Insertion Depth: (2,64mm) .104" to (3,17mm) .125" Insertion Force: (Single contact only)

oz (1,39N) avg. Withdrawal Force: (Single contact only) 3oz (0,83N) avg.

**RoHS Compliant:** 

Note: This Series is non-standard, non-returnable.

## **SPECIFICATIONS**

## Mates with: FLE\*, SFMC\*

For complete specifications see www.samtec.com?FFMD


**FFMD** 


Insulator Material: Black Glass Filled Polyester Terminal: BeCu

Plating: Sn over 50μ" (1,27μm) Ni Wire: 30 AWG Current Rating: 0.5A Operating Temp Range: -40°C to +105°C RoHS Compliant: Yes

\*Note: Standard FFMD callout will not mate with FLE, SFMC.
Must use gold plated callouts.
(See drawing on web.)
When mated with a socket,
Wire 1 mates with Pin 2;

Wire 2 mates wth Pin 1, etc. Note: This Series is non-standard, non-returnable.





Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM