

## 1734078 -4 Product Details



**1734078 -4**

[Active](#)

### Standard Board Mount Connectors

[Always EU RoHS/ELV Compliant](#) ([Statement of Compliance](#))

#### Product Highlights:

- ? Number of Positions = 15
- ? Receptacle
- ? PCB Mount Angle = Right Angle
- ? Product Series = HD -22
- ? With Mating Connector Lock

[View all Features](#) | [Find Similar Products](#)

**Live Product Chat** US Only  
8:30am - 5pm ET, Mon - Fri

#### Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling Product Feature Selector](#)
- [Contact Us About This Product](#)

### Documentation & Additional Information

#### Product Drawings:

- ? [D Sub 15Pos. Right Angle RCPT Connector](#) (PDF, English)

#### Catalog Pages/Data Sheets:

- ? None Available

#### Product Specifications:

- ? None Available

#### Application Specifications:

- ? None Available

#### Instruction Sheets:

- ? None Available

#### CAD Files:

- ? None Available

#### Additional Information:

- ? [Product Line Information](#)

#### Related Products:

- ? [Tooling](#)

[List all Documents](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- ? [Number of Positions](#) = 15
- ? [Gender](#) = Receptacle
- ? [PCB Mount Angle](#) = Right Angle
- ? [Product Series](#) = HD -22
- ? [Mating Connector Lock](#) = With
- ? [Mating Connector Lock Type](#) = Screwllocks
- ? [PCB Retention Feature](#) = Yes
- ? [Shell Type](#) = Front Metal Shell
- ? [Shell Size](#) = 1
- ? [Footprint \(mm \[in\]\)](#) = 3 [1.18]
- ? [PCB Thickness \(in \[mm\]\)](#) = 0.039 - 0.071 [1.00 - 1.80]
- ? [Grounding Indents](#) = Without
- ? [Grounding Straps](#) = Without
- ? [PCB Mount Style](#) = Thru Hole
- ? [Color Code](#) = None
- ? Sealed = No
- ? Profile = Standard
- ? Mounting Hole Diameter (mm [in]) = 3.20 [1.26]
- ? Color = Blue
- ? Shell Material = SPCC
- ? Screw Material = Brass
- ? Comment = With screw.

#### Mechanical Attachment:

- ? [Panel Attachment](#) = Without
- ? Boardlock Material = Brass
- ? Screw Plating = Nickel

#### Termination Related Features:

- ? [Grounding Clips](#) = Without
- ? [Termination \(Solder\) Post Length \(mm \[in\]\)](#) = 3.18 [0.125]
- ? [Solder Tail Contact Plating](#) = Bright Tin over Nickel

#### Body Related Features:

- ? [PCB Retention Method](#) = Boardlock(s)
- ? Shell Plating = Nickel

#### Contact Related Features:

- ? [Contact Mating Area Plating](#) = Gold Flash
- ? Contact Material = Brass

#### Housing Related Features:

- ? Housing Flammability Rating = UL 94V -0
- ? Housing Material = Thermoplastic High Temperature

#### Industry Standards:

- ? [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- ? [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

#### Conditions for Usage:

- ? High Temperature Housing = Yes

#### Packaging Related Features:

- ? Packaging Quantity = 100
- ? Packaging Method = Tray

#### Other:

- ? Brand = AMP