



Straight Mounting Connectors

Straight Mounting Connectors

Material and Finish:

Front Shell—Steel, tin plated

Housing—Black glass-filled polyester

Flammability—UL 94V-0

Contact Material—

Pin—Phosphor bronze

Socket—Phosphor bronze

Contact Area Plating—0.76µm Gold

Current Rating—6A max.

Insulation Resistance—

5000 MΩ min.

Dielectric Strength—1000V AC

Temperature Rating—

-55°C to +105°C

Plug with Boardlocks — Solder Termination

No of Ways	3mm Hole	4-40 Inserts	4-40 Screwlocks	M3 Inserts	M3 Screwlocks
9	—	1-338309-2	3-338309-2	2-338309-2	4-338309-2
15	—	1-338310-2	3-338310-2	2-338310-2	4-338310-2
25	—	1-338311-2	3-338311-2	2-338311-2	4-338311-2
37	—	1-338312-2	3-338312-2	2-338312-2	4-338312-2

Socket with Boardlocks — Solder Termination

No of Ways	3mm Hole	4-40 Inserts	4-40 Screwlocks	M3 Inserts	M3 Screwlocks
9	—	1-338313-2	3-338313-2	2-338313-2	4-338313-2
15	—	1-338314-2	3-338314-2	2-338314-2	4-338314-2
25	—	1-338315-2	3-338315-2	2-338315-2	4-338315-2
37	—	1-338316-2	3-338316-2	2-338316-2	4-338316-2

Plug without Boardlocks — Solder Termination

No of Ways	3mm Hole	4-40 Inserts	4-40 Screwlocks	M3 Inserts	M3 Screwlocks
9	5-338309-2	6-338309-2	8-338309-2	7-338309-2	9-338309-2
15	5-338310-2	6-338310-2	8-338310-2	7-338310-2	9-338310-2
25	5-338311-2	6-338311-2	8-338311-2	7-338311-2	9-338311-2
37	5-338312-2	6-338312-2	8-338312-2	7-338312-2	9-338312-2

Socket without Boardlocks — Solder Termination

No of Ways	3mm Hole	4-40 Inserts	4-40 Screwlocks	M3 Inserts	M3 Screwlocks
9	5-338313-2	6-338313-2	8-338313-2	7-338313-2	9-338313-2
15	5-338314-2	6-338314-2	8-338314-2	7-338314-2	9-338314-2
25	5-338315-2	6-338315-2	8-338315-2	7-338315-2	9-338315-2
37	5-338316-2	6-338316-2	8-338316-2	7-338316-2	On Enquiry