



Search:



Products

Catalogs

Search

Customer Support

About Cannon

Home



## Standard D (Machined)

**PART NUMBER: DBM25SB**

<b>Where Sold</b>	Asia Pacific, Europe, Americas
<b>Product Group</b>	D-Subminiature
<b>Product Sub-Family</b>	D-Sub Standard
<b>Component Type</b>	Connector
<b>Application Type</b>	Military/High Reliability
<b>Cable or PC Board</b>	PC Board
<b>Gender</b>	Receptacle
<b>Number of Signal Pins</b>	25
<b>Number of Size 8 contacts</b>	0
<b>Straight or Right Angle</b>	Straight
<b>Contact Plating</b>	Gold over Nickel
<b>Shell Plating</b>	Yellow Chromate over Zinc
<b>Hardware</b>	3,05 (.120) Through Holes
<b>Contact Termination</b>	1,02 (.040) dia, 3,23 (.127) Extention
<b>Shell Size</b>	DB
<b>Temperature Rating</b>	-55°C to +125°C
<b>Current Capacity</b>	5 A
<b>Contact Resistance</b>	8 milli ohms max.
<b>Dielectric Withstanding Voltage</b>	1250 V AC at Sea Level
<b>Reference Industry Specifications</b>	Mil-PRF-24308
<b>Insulator Material</b>	Polyester
<b>Contact Material</b>	Copper Alloy
<b>Shell Material</b>	Steel

- [Sales Support](#)
- [Ask a Specialist](#)
- [Product Home](#)
- [Stock Check](#)
- [Dimensional Drawing](#)

[Sign In](#) | [Contact Us](#) | [Legal Disclaimer](#) | [Privacy Policy](#) | [Home](#)

© 2006 ITT Industries