

This document was generated on 11/19/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0424751041

Status: Active
Overview: minifit bmi

Description: 4.20mm (.165") Pitch Mini-Fit BMI™ Plug Housing, Dual Row With Panel Mount Ears,

Black, UL 94V-0, 10 Circuits

Documents:

3D Model Product Specification PS-5556-002 (PDF)
Drawing (PDF) RoHS Certificate of Compliance (PDF)

General
Product Family Crimp Housings

Series 42475 Application Power

Comments Current = 13A max. per circuit when header is mated

to a receptacle loaded with <u>45750</u> series terminals crimped to 16 AWG wire. . See Molex product specification PS-45750-001 for additional current de-

rating information.

Physical

Circuits (maximum) 10 Color - Resin Natural Gender Male Glow-Wire Compliant Nο Material - Resin Nylon Number of Rows 2 Packaging Type Bag Panel Mount Yes

Pitch - Mating Interface 4.20mm (.165")

Stackable No

Temperature Range - Operating -40°C to +105°C

Electrical

Current - Maximum per Contact 13A

Material Info

Country of Origin US

Reference - Drawing Numbers

Packaging Specification PK-42474-001, PK-5557-003

Product Specification PS-5556-002
Sales Drawing SD-42475-***1
Test Summary TS-5556-002

Series image - Reference only

China RoHS

EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Not Reviewed

Not Reviewed

Low-Halogen Status

Not Reviewed

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
For a multiple part number RoHS Certificate of Compliance, <u>click here</u>

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

Search Parts in this Series

42475Series

Mates With

 $\frac{44475}{5557d} \,, \frac{44516}{1000} \,, \frac{42474}{1000} \, \text{Receptacle Housing, } \frac{42385}{1000} \,$

Receptacle Header

Use With

46012 Mini-Fit Plus HCS™ Crimp Terminal, 5558 Mini-Fit™ Crimp Terminal

This document was generated on 11/19/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION