

This document was generated on 01/12/2011

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0520040810
Status: Active - Custom

Overview: wire trap

Description: 1.50mm (.059") Pitch Wire Trap, Push-Cover Style, Vertical, 8 Circuits

Documents:

3D Model Product Specification PS-52004-002 (PDF)
Drawing (PDF) RoHS Certificate of Compliance (PDF)

Product Specification PS-52004-001 (PDF)

General

Product Family Ribbon Cable / Wire Trap Connectors

 Series
 52004

 Comments
 Push-Cover

 Component Type
 One Piece

 Glow-Wire Compliant
 No

 Overview
 wire trap

Product Name Board-In, Wire Trap

Physical

Circuits (Loaded) 8
Entry Angle Vertical
Lock to Mating Part None
Number of Rows 1
PCB Retention Yes

PCB Thickness - Recommended 1.60mm (.063")
Packaging Type Tray

Pitch - Mating Interface 1.50mm (.059")

Polarized to Mating Part

Polarized to PCB

Stackable

Surface Mount Compatible (SMC)

No

Temperature Range - Operating -40°C to +105°C
Wire Insulation Diameter 1.50mm (.059") max.

Wire Size AWG 24, 26
Wire/Cable Type Ribbon Cable

Electrical

Current - Maximum per Contact 2.5A Voltage - Maximum 150V

Material Info

Reference - Drawing Numbers

Product Specification PS-52004-001, PS-52004-002

Sales Drawing SD-52004-**10

Series image - Reference only

EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Not Reviewed
Low-Halogen Status
Not Reviewed

China RoHS

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
For a multiple part number RoHS Certificate of Compliance, <u>click here</u>

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

Search Parts in this Series

52004Series

Mates With

N/A

Use With

Topcoated ribbon cable

This document was generated on 01/12/2011

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION