

This document was generated on 02/22/2011 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: Status:	Active picoflex		
Overview: Description:			
Documents:			
3D Model		Product Specification PS-99020-0011 (PDF)	
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	
Agency Certific	cation		image - Reference only
UL		E29179	
General			EU RoHS China RoHS ELV and RoHS
Product Family		PCB Headers	Compliant
Series		90814	REACH SVHC
Application		Signal, Wire-to-Board	Contains SVHC: No
Application Tooling Part Link		690081070	Low-Halogen Status
Comments		Low Profile SMT	Not Low-Halogen
Overview		picoflex	
Product Name		Picoflex®	Need more information on product
		environmental compliance?	
Physical			Email productcompliance@molex.com
Breakaway		No	For a multiple part number RoHS Certification
Circuits (Loaded)		4	Compliance, <u>click here</u>
Color - Resin		Black, Natural	
Durability (mating cycles max)		30	Please visit the Contact Us section for any
First Mate / Last Break		No	non-product compliance questions.
Flammability		94V-0	
Glow-Wire Complia	ant	Yes	
Guide to Mating Part		No	
Keying to Mating Part		None	Search Parts in this Series
Lock to Mating Part		Yes	90814Series
Material - Metal		Brass	<u>90014</u> 3enes
Material - Plating Mating		Tin	
Material - Resin		High Temperature Thermoplastic	Mates With
Number of Rows		1	90327 IDT Connector
Orientation		Vertical	
PCB Locator		Yes	Application Tooling FAQ
PCB Retention		Yes	Tooling specifications and manuals are
PCB Thickness - Recommended		1.60mm (.063")	found by selecting the products below.
Packaging Type		Adhesive Tape on Reel	Crimp Height Specifications are then
Pitch - Mating Interface		1.27mm (.050")	contained in the Application Tooling
Pitch - Termination Interface			Specification document.
		1.27mm (.050")	Global
Plating min - Mating		3.048µm (120µ")	Description Product #
Plating min - Termination		3.048µm (120µ")	Extraction Tool <u>0690081070</u>
Polarized to Mating Part		Yes	(Plastic) for 90327
Polarized to PCB		Yes Onen Ende	Connector, 4-26
Shrouded		Open Ends	Circuit
Stackable		No	
Surface Mount Con		Yes	
Temperature Rang Termination Interfa	1 0	-40°C to +105°C Surface Mount	
Electrical	0.1.1	2.44	
Current - Maximum	per Contact	2.4A	

Voltage - Maximum

250V AC/DC

Material Info

Reference - Drawing Numbers Product Specification Sales Drawing

PS-99020-0011 SDA-90814

This document was generated on 02/22/2011 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION