

This document was generated on 02/22/2011

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0908140224

Status: Active
Overview: picoflex

Description: 1.27mm (.050") Pitch Picoflex® PF-50 Header, Vertical, Low Profile, Surface Mount, 24

Circuits, Glow Wire Compatible

Documents:

3D Model Product Specification PS-99020-0011 (PDF)
Drawing (PDF) RoHS Certificate of Compliance (PDF)

Agency Certification

UL E29179

General

Product Family PCB Headers Series 90814

Application Signal, Wire-to-Board

Application Tooling Part Link 690081070
Comments Low Profile SMT
Overview picoflex
Product Name Picoflex®

Physical

Breakaway No Circuits (Loaded) 24

Color - Resin Black, Natural

Durability (mating cycles max) 30 First Mate / Last Break Nο Flammability 94V-0 Glow-Wire Compliant Yes Guide to Mating Part No Keying to Mating Part None Lock to Mating Part Yes Material - Metal Brass Material - Plating Mating

Material - Resin High Temperature Thermoplastic

Number of Rows 1
Orientation Vertical
PCB Locator Yes
PCB Retention Yes

PCB Thickness - Recommended 1.60mm (.063")
Packaging Type Adhesive Tape on Reel


Pitch - Mating Interface 1.27mm (.050")
Pitch - Termination Interface 1.27mm (.050")
Plating min - Mating 3.048µm (120µ")
Plating min - Termination 3.048µm (120µ")

Polarized to Mating Part
Polarized to PCB
Shrouded
No
Stackable
No
Surface Mount Compatible (SMC)
No
N/A

Temperature Range - Operating -40°C to +105°C
Termination Interface: Style Surface Mount

Electrical

Current - Maximum per Contact 1.2A



EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Contains SVHC: No
Low-Halogen Status

Not Low-Halogen

China RoHS

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
For a multiple part number RoHS Certificate of Compliance, <u>click here</u>

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

Search Parts in this Series

90814Series

Mates With

90327 IDT Connector

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

DescriptionProduct #Extraction Tool0690081070

(Plastic) for 90327 Connector, 4-26

Circuit

Voltage - Maximum 250V

Material Info

Reference - Drawing Numbers

Product Specification PS-99020-0011 Sales Drawing SDA-90814

This document was generated on 02/22/2011

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION