

This document was generated on 11/18/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>0908143826</u>		
Status:	Active		
Overview:	picoflex		
Description:		Picoflex® PF-50 SMT Header, Vertical, Low Profile, Surface	A SUPPOR
Description.		ts, Glow Wire Compatible	
	Mount, Gold, 20 Circui	is, Glow Wile Compatible	
_			
Documents:			
<u>3D Model</u>		Product Specification PS-99020-0011 (PDF)	V V
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	
			— Series
Agency Certificat	ion		image - Reference only
UL		E29179	
0E		223173	EU RoHS China RoHS
General			ELV and RoHS
Product Family		PCB Headers	Compliant
Series		90814	REACH SVHC
			Not Reviewed
Application	at Lin L	Signal, Wire-to-Board	
Application Tooling Pa		690081070	Low-Halogen Status Not Reviewed
Comments		Low Profile SMT	Not Reviewed
Overview		picoflex	Need more information on product
Product Name		Picoflex®	environmental compliance?
Physical			
		No	Email productcompliance@molex.com
Breakaway		No	For a multiple part number RoHS Certificate of
Circuits (Loaded)		26	Compliance, <u>click here</u>
Color - Resin		Natural	
Durability (mating cycle		100	Please visit the <u>Contact Us</u> section for any
First Mate / Last Break	< C	No	non-product compliance questions.
Flammability		94V-0	
Glow-Wire Compliant		Yes	
Guide to Mating Part		No	
Keying to Mating Part		None	Search Parts in this Series
Lock to Mating Part		Yes	<u>90814</u> Series
Material - Metal		Brass	
Material - Plating Matir	ng	Gold	Mates With
Material - Resin	0	High Temperature Thermoplastic	90327 IDT Connector
Number of Rows		1	
Orientation		Vertical	
PCB Locator		Yes	
PCB Retention		Yes	
PCB Thickness - Reco	ommended	1.60mm (.063")	
Packaging Type		Tube	
Pitch - Mating Interface	9	1.27mm (.050")	
Pitch - Termination Inte		1.27mm (.050")	
Plating min - Mating		0.762µm (30µ")	
Plating min - Terminati	ion		
		0.102µm (4µ")	
Polarized to Mating Pa	41 L	Yes	
Polarized to PCB		Yes	
Shrouded		Open Ends	
Stackable		No	
Surface Mount Compa		Yes	
Temperature Range -		-40°C to +105°C	
Termination Interface:	Style	Surface Mount	
Ele etale - l			
Electrical	a	A 44	
L Curront Movimum no	r (Contact	2.44	

Current - Maximum per Contact

2.4A

Voltage - Maximum	250V AC/DC
Material Info Country of Origin	IE
Reference - Drawing Numbers Packaging Specification Product Specification Sales Drawing	PK-90814-001 PS-99020-0011 SDA-90814

This document was generated on 11/18/2010 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION