


[> PN Search](#)
[Home page](#)
[Product quick search](#)

P/N Search




[Product type search](#)
[Alphabetical list](#)
[Connection type](#)
[Markets / Applications](#)
[Product finder](#)
[Literature](#)
[Services](#)
[Contact us](#)
[Registered users](#)
[Forgot password ?](#)
[Register now](#)

**Top Entry DIP ZIF FPC/FFC Connector, 1.25mm, Kinked Terminal**  
SLEM23S-2



**FCI brings you more**
 [Contact our sales/technical support](#)
 [Sample request](#)
 [€ Price request](#)
 [Check distributor stock](#)




[> Customer Drawing](#)
[> Product Specification](#)

Not Available

Not Available

[www.foehrenbach.be](http://www.foehrenbach.be)
[Americas](#)
[Asia Pacific](#)

### Features Selected

**Orientation** Straight

**# of Positions** 23

### Other Properties

**Voltage Rating** 200V AC/DC

**Contact Resistance** 30 milli ohms max

**Insulation Resistance** 1000M-ohms min

**Withstanding Voltage** 500V AC for 1 minute

**Durability (Mating Cycles)** 20 cycles

**Vibration per JIS C 0040** No discontinuity > 1 micro second

**Salt Spray per JIS C 0023** Contact resistance 50 milli ohms max.

**Damp Heat per JIS C 0022** Contact Resistance 50 milli ohms max, Insulation Resistance 100M ohms min

**Temperature Cycling per JIS C 0025** Contact resistance 50 milli ohms max.

**Temperature Range** -55 to +85 c

**Packaging Type** Tray

**Cable Type** FPC/FFC

**Cable Insertion** ZIF

**PCB Mounting** DIP

**Housing Material** Glass Reinforced PBT, UL94 V-0

**Contact Material** Phosphor Bronze, Tin alloy plated

**Current Rating** 1A AC/DC