
My Account

Home > Products > By Type > Ribbon, SATA/SAS/Mini -SAS & Flat Flex Wire Connectors > Product Feature Selector > Product Details

487117 - 9 Product Details





Flexible Film Contacts

Always EU RoHS/ELV Compliant (Statement of Compliance

Product Highlights:

- ? Socket
- Contact Type = Receptacle, high pressure
- 2.54 mm Centerline
- ? Wire/Cable Type = Flexible Flat Conductor Cable
- Tin Contact Mating Area Plating Material

View all Features | Find Similar **Products**

Live Product Chat US Onl

Quick Links

Check Pricing & <u>Availability</u> Search for Tooling View Housings (170) Product Feature <u>Selector</u> Contact Us About This Product

Documentation & Additional Information

Product Drawings:

? RECEPTACLE CONTACT, HIGH PRESSURE (PDF, English)

Catalog Pages/Data Sheets:

? None Available

Product Specifications:

? None Available

Application Specifications:

None Available

Instruction Sheets:

? None Available

CAD Files:

? None Available

Additional Information:

Product Line Information

Related Products:

- ? Tooling
- ? Housings (170)

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- ? Pin/Socket = Socket
- Wire/Cable Type = Flexible Flat Conductor
- ? Wire Termination Type = Sequential
- ? Comment = High pressure receptacle contacts are recommended for a maximum connector size of 15 positions.

Termination Related Features:

? Solder Tail Contact Plating = Gold Flash

Body Related Features:

- ? Centerline (mm [in]) = 2.54 [0.100]
- ? Conductor Width (mm [in]) = 1.19 [0.047]

Contact Related Features:

- ? Contact Type = Receptacle, high pressure
- ? Contact Mating Area Plating Material = Tin

Industry Standards:

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- 2 Lead Free Solder Processes = Not relevant for lead free process
- ? RoHS/ELV Compliance History = Always was RoHS compliant

Packaging Related Features:

? Packaging Method = Strip

? Brand = AMP

Provide Website Feedback | Contact Customer Support