

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Connector Type = Housing
- Drawer Connector = No
- Termination Method to Wire/Cable = IDC
- Product Line = CT
- CSA File Number = LR 7189

Electrical Characteristics: • Contact Current Rating (A) = 2

- Operating Voltage Reference = AC/DC
- Operating Voltage (V) = 125

Body Related Features: • Centerline (mm [in]) = 2.00 [0.079]

- Number of Positions = 5
- Number of Rows = 1
- Mating Retention = Without
- Length (X-Axis) (mm [in]) = 12.00 [0.472]
- Width (Z-Axis) (mm [in]) = 4.60 [0.181]
- Profile Height (Y-Axis) (mm [in]) = 5.10 [0.200]

Contact Related Features:

- Contact Plating, Mating Area, Material = Pre-Tin
- Preloaded = Yes
- Contact Type = Socket

List all Documents

- Housing Related Features: Connector Style = Receptacle
 - Housing Color = Black
- UL Flammability Rating = UL 94V-0

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Not relevant for lead free process RoHS/ELV Compliance History = Always was RoHS compliant
- UL Rating = E28476

Conditions for Usage:

- Applies To = Wire
- Wire Gauge, Applicable (AWG) = 26 28
- Operating Temperature (°C [°F]) = -30 +105 [-22 +221]
- Accepts Wire Insulation Diameter, Range (mm [in]) = 0.85 1.05 [0.0334 0.041]

Operation/Application:

• Application Use = Wire-to-Board, Wire-to-Board/Wire-to-Wire, Wire-

Packaging Related Features:

Other:

Brand = AMP

BOOKMARK # 19 49 ...

Corporate Information Ouick Links Who We Are Investors News Room Supplier Portal Careers

Check Distributor Inventory Cross Reference Find Documents & Drawings Product Compliance Support Center Customer Support Email or Chat with Us Find a Phone Number Search Knowledge Base Manage Your Account





