# Product Details for 5406874

# No Image Available

# 2.16 [.085] Printed Circuit Board Connectors

RoHS Compliant (Statement of Compliance)

# 5406874 -1

# Product Highlights:

? Receptacle

- 1

- Number of Positions = 50
- ? PCB Mount Style = Vertical
- Standard Orientation
- ? Low Profile

View all Features

#### **Quick Links**

Check Pricing &
Availability
Search for Tooling
Product Feature
Selector
Contact Us About
This Product

# 

# **Documentation & Additional Information**

#### **Product Drawings:**

? RECEPTACLE ASSEMBLY,50 POSITION, BOARDLOCK,SHIELDED,... (PDF, English)

#### Catalog Pages/Data Sheets:

? None Available

# **Product Specifications:**

? None Available

# **Application Specifications:**

? None Available

#### Instruction Sheets:

? None Available

#### CAD Files:

? None Available

#### Additional Information:

? Product Line Information

#### Related Products:

? Tooling

List all Documents

# **Product Features**

(Please use the Product Drawing for all design activity)

# **Product Type Features:**

- ? <u>Gender</u> = Receptacle
- ? Number of Positions = 50
- ? PCB Mount Style = Vertical
- ? Orientation = Standard
- ? Profile = Low
- ? Shielded = Yes
- ? Mating Connector Lock = With
- ? Mating Connector Lock Type = Bail Lock
- ? Special PCB Retention = With
- ? Special PCB Retention Method = Boardlock
- ? Grounded = No
- ? Color = Black
- ? Shield Material = Die Cast Metal
- ? Boss on Shield = With

#### **Mechanical Attachment:**

- ? Panel Attachment = With
- Panel Attachment Style = Rear Mount

#### **Termination Related Features:**

- 7 Termination Post Length (mm [in]) = 3.68 [0.145]
- ? Solder Tail Plating = Tin

# **Body Related Features:**

<sup>2</sup> Shield Plating = Nickel

#### **Contact Related Features:**

- ? Contact Mating Area Plating = Gold over Nickel
- ? Contact Material = Copper Alloy

# **Housing Related Features:**

? Housing Material = Thermoplastic

# **Industry Standards:**

- ? Rohs/ELV Compliance = Rohs compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260° C, Wave solder capable to 265°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

# Operation/Application:

? Application = SCSI

#### Other

? Brand = AMP